

# 屋内照明器具特性

品番 (品名)	LGB58013Z	
光源	LDA8L-G/K60E/S/W ×1	810.0 lm
管理番号	K0132096(0)DB1	
BZ分類	BZ6/0.7/BZ5/2.8/BZ6	

器具効率	89%	天井	80%				70%				50%				30%				0%			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	22%	反射率	床	10%				10%				10%				10%				0%		
下方光束	67%		室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	46	35	28	24	44	34	27	23	39	31	26	22	36	29	24	20	17			
		0.8	54	44	37	32	52	42	36	31	47	39	33	29	42	36	31	27	23			
		1.0	60	50	43	38	57	48	42	37	51	44	39	34	46	41	36	32	28			
		1.25	65	56	49	44	62	54	47	43	56	49	44	40	50	45	41	37	32			
下方投影面積	c m <sup>2</sup>	1.5	68	60	54	48	65	58	52	47	59	53	48	44	53	48	44	41	36			
		2.0	73	66	60	55	70	63	58	54	63	58	54	50	57	53	50	47	40			
取付高さ	器具間隔最大限		2.5	76	70	65	60	73	67	62	58	66	62	58	54	60	56	53	50	44		
	横方向 (A)	縦方向 (B)	3.0	78	73	68	64	75	70	66	62	68	64	61	58	62	59	56	53	46		
H m	1.46 H m	1.46 H m	4.0	81	77	73	69	78	74	70	67	71	68	65	62	65	62	60	57	50		
			5.0	83	79	76	72	80	76	73	70	73	70	67	65	66	64	62	60	53		
			7.0	85	82	79	77	82	79	76	74	75	73	71	69	69	67	65	64	56		
			10.0	87	85	82	80	83	81	79	78	77	75	73	72	70	69	68	66	58		

