

屋内照明器具特性	
品番 (品名)	L S E W5 0 2 8
光源	LED2700_70_450 ×1 450.0 lm
管理番号	K0159976 (0) D 1
BZ分類	BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 7	0 . 6	6 2	5 1	4 4	3 9	6 1	5 0	4 4	3 9	5 9	4 9	4 3	3 9	5 7	4 8	4 3	3 9	3 7				
			0 . 6 3	0 . 8	7 2	6 2	5 6	5 1	7 1	6 2	5 5	5 1	6 9	6 1	5 5	5 0	6 6	5 9	5 4	5 0	4 8				
			0 . 5 6	1 . 0	7 9	7 0	6 4	5 9	7 8	6 9	6 3	5 9	7 5	6 8	6 2	5 8	7 3	6 7	6 2	5 8	5 6				
				1 . 2 5	8 5	7 7	7 1	6 6	8 4	7 6	7 0	6 6	8 1	7 5	7 0	6 6	7 8	7 3	6 9	6 5	6 3				
下方投影面積		c m ²	1 . 5	8 9	8 2	7 6	7 2	8 7	8 1	7 5	7 1	8 5	7 9	7 4	7 1	8 2	7 7	7 3	7 0	6 8					
			2 . 0	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 9	9 0	8 5	8 1	7 8	8 7	8 3	8 0	7 7	7 5					
取付 高さ	器具間隔最大限		2 . 5	9 7	9 2	8 8	8 4	9 5	9 1	8 7	8 4	9 3	8 9	8 5	8 3	9 0	8 7	8 4	8 2	7 9					
	横方向 (A) 縦方向 (B)		3 . 0	9 9	9 4	9 1	8 8	9 7	9 3	9 0	8 7	9 5	9 1	8 8	8 6	9 2	8 9	8 7	8 5	8 2					
H m	1 . 2 0 H m	1 . 1 9 H m	4 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 2	9 7	9 5	9 2	9 0	9 5	9 3	9 1	8 9	8 6					
			5 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 2	8 9					
			7 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 2					
			1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	9 9	9 9	9 8	9 7	9 4					

