

屋内照明器具特性

品番 (品名)	NND26150K															
光源	LEDALL_90_405.9 x1 405.9 1m															
管理番号	K0147724(0)DD1															
BZ分類	BZ3/8.5/BZ4															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	6%	室指数	照明率 (X0.01)																ZCM		
下方光束	94%																				
保守率	良 中 否 0.88 0.86 0.81	0.6	63	53	46	41	62	52	46	41	59	50	45	41	57	49	44	40	38		
		0.8	72	63	56	51	71	62	56	51	68	60	55	50	65	59	54	50	48		
		1.0	79	70	63	59	77	69	63	58	74	67	61	57	71	65	60	57	54		
		1.25	84	76	70	65	82	75	69	65	79	72	68	64	75	70	66	63	60		
下方投影面積	c m ²	1.5	87	80	75	70	85	79	74	70	82	76	72	68	79	74	70	67	64		
		2.0	92	86	81	77	90	85	80	76	86	82	78	75	83	79	76	73	70		
取付高さ	器具間隔最大限		2.5	95	90	85	82	93	88	84	81	89	85	82	79	86	83	80	78	74	
	横方向 (A)	縦方向 (B)	3.0	97	92	89	85	95	91	87	84	91	88	85	82	88	85	83	80	77	
H m	1.08 H m	0.95 H m	4.0	99	96	93	90	97	94	91	89	94	91	89	87	90	88	86	84	81	
			5.0	101	98	95	93	99	96	94	92	95	93	91	89	92	90	88	87	83	
			7.0	102	100	98	96	101	99	97	95	97	95	94	92	94	92	91	90	86	
			10.0	104	102	101	99	102	100	99	98	98	97	96	95	95	94	93	92	88	

