

# 屋内照明器具特性

品番 (品名)	LGB11601Z														
光源	LDA8L-G/K60E/S/W ×4										810.0 lm				
管理番号	K0129913(0)DB1														
BZ分類	BZ7														

器具効率	86%	天井	80%				70%				50%				30%				0%		
	上方光束		35%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		51%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.63	0.6	40	30	23	18	37	28	22	17	32	24	19	15	27	21	16	13	9	
	中	0.6	0.8	48	37	30	25	44	35	28	24	38	30	25	21	32	26	22	18	13	
	否	0.56	1.0	53	43	36	30	49	40	33	28	42	35	29	25	35	30	25	22	16	
			1.25	57	48	41	36	53	45	39	34	46	39	34	30	39	33	29	26	19	
下方投影面積			1.5	61	52	45	40	57	49	43	38	49	42	37	33	41	36	32	29	22	
			2.0	66	58	52	47	61	54	49	44	53	47	43	39	45	41	37	34	26	
取付高さ	器具間隔最大限		2.5	69	62	56	52	64	58	53	49	55	51	47	43	47	44	40	37	28	
	横方向 (A)	縦方向 (B)	3.0	71	65	60	55	66	61	56	52	57	53	49	46	49	46	43	40	31	
Hm	1.45Hm	1.45Hm	4.0	74	69	65	61	69	65	61	57	60	57	53	51	52	49	46	44	34	
			5.0	76	72	68	64	71	67	64	61	62	59	56	54	53	51	49	47	36	
			7.0	78	75	72	69	73	70	68	65	64	62	60	57	56	54	52	50	39	
			10.0	80	77	75	73	75	73	71	69	66	64	62	61	57	56	55	53	42	

