

屋内照明器具特性	
品番 (品名)	NND26150K
光源	LEDGREEN_90_297.9 ×1 297.9 1 m
管理番号	K0147721(0)DD1
BZ分類	BZ3/4.5/BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	8%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	92%																																																						
保守率	良 中 否 0.88 0.86 0.81	0.6	62	51	45	40	61	51	44	40	58	49	43	39	55	48	42	39	36																																				
		0.8	71	62	55	50	70	61	54	50	67	59	53	49	64	57	52	48	46																																				
		1.0	78	69	62	57	76	67	61	57	72	65	60	56	69	63	59	55	52																																				
		1.25	83	75	69	64	81	73	68	63	77	71	66	62	74	69	64	61	58																																				
下方投影面積 等価発光面積	c m ²	1.5	86	79	73	69	84	78	72	68	81	75	70	67	77	72	69	65	62																																				
		2.0	91	85	80	76	89	83	79	75	85	81	77	73	82	78	74	72	68																																				
		2.5	94	89	84	81	92	87	83	80	88	84	81	78	84	81	78	76	72																																				
取付高さ H m	器具間隔最大限		横方向 (A)		縦方向 (B)																																																		
	1.08H m	0.98H m																																																					
		4.0	98	95	92	89	96	93	90	88	92	90	87	85	89	87	84	83	78																																				
		5.0	100	97	94	92	98	95	93	90	94	92	90	88	90	88	87	85	81																																				
		7.0	102	99	97	95	100	98	96	94	96	94	93	91	92	91	89	88	84																																				
		10.0	103	101	100	98	101	100	98	97	97	96	95	94	93	92	92	91	86																																				

