

屋内照明器具特性

品番 (品名)	NND26150K															
光源	LEDBLUE_90_72 x1 72.0 l m															
管理番号	K0147722 (0) DD 1															
BZ分類	BZ5 / 8.5 / BZ6															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	30 %																			
下方光束	70 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.88	0.6	5.4	4.2	3.5	3.0	5.1	4.0	3.4	2.9	4.6	3.7	3.1	2.7	4.1	3.4	2.9	2.5	2.2
		0.86	0.8	6.2	5.1	4.4	3.8	5.9	4.9	4.2	3.7	5.3	4.5	3.9	3.5	4.7	4.1	3.6	3.2	2.8
		0.81	1.0	6.8	5.8	5.0	4.5	6.5	5.5	4.9	4.3	5.8	5.0	4.5	4.0	5.2	4.6	4.1	3.8	3.2
			1.25	7.3	6.4	5.7	5.1	7.0	6.1	5.5	5.0	6.2	5.6	5.0	4.6	5.6	5.0	4.6	4.3	3.6
下方投影面積		cm ²																		
等価発光面積		cm ²																		
取付高さ	器具間隔最大限		2.5	8.5	7.9	7.3	6.9	8.1	7.5	7.0	6.6	7.3	6.8	6.4	6.1	6.5	6.2	5.9	5.6	4.7
	横方向 (A)	縦方向 (B)	3.0	8.8	8.2	7.7	7.3	8.3	7.8	7.4	7.0	7.5	7.1	6.7	6.4	6.7	6.4	6.1	5.9	5.0
Hm	1.10Hm	0.98Hm	4.0	9.1	8.6	8.2	7.8	8.6	8.2	7.8	7.5	7.8	7.5	7.1	6.9	7.0	6.7	6.5	6.3	5.3
			5.0	9.3	8.8	8.5	8.1	8.8	8.4	8.1	7.8	8.0	7.7	7.4	7.2	7.2	6.9	6.7	6.5	5.6
			7.0	9.5	9.2	8.9	8.6	9.0	8.8	8.5	8.2	8.2	8.0	7.7	7.6	7.4	7.2	7.0	6.9	5.9
			10.0	9.7	9.4	9.2	9.0	9.2	9.0	8.8	8.6	8.4	8.2	8.0	7.9	7.6	7.4	7.3	7.2	6.1

