

屋内照明器具特性

品番 (品名)		NTS62714S+NTS90101																			
光源		LED2700_70_410 x1 410.0 lm																			
管理番号		K0156488 (1) DJ 1																			
B Z 分類		BZ1																			
器具効率		102 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
上方光束		0 %		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束		102 %		床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 0.67 中 0.63 否 0.56	0.6	102	100	98	97	102	100	98	97	101	99	98	97	101	99	98	97	96	
			0.8	104	102	100	99	104	101	100	99	103	101	100	99	102	100	99	98	98	
			1.0	105	103	102	100	105	103	101	100	103	102	101	100	103	101	100	99	99	
下方投影面積		c m ²	1.25	106	104	103	102	105	104	102	101	104	103	102	101	103	102	101	100	99	
等価発光面積		c m ²	1.5	107	105	104	103	106	104	103	102	105	103	102	101	103	102	101	101	100	
			2.0	108	106	105	104	107	105	104	103	105	104	103	103	104	103	102	102	100	
取付高さ		器具間隔最大限	2.5	108	107	106	105	107	106	105	104	106	105	104	103	104	103	103	102	101	
H m		横方向 (A)	3.0	109	107	106	106	108	107	106	105	106	105	104	104	104	104	103	103	101	
		縦方向 (B)	4.0	109	108	107	107	108	107	107	106	106	106	105	105	104	104	104	103	101	
			5.0	109	109	108	107	108	108	107	107	106	106	105	105	105	104	104	103	101	
			7.0	110	109	109	108	109	108	108	107	107	106	106	106	105	104	104	104	101	
			10.0	110	101	101	09	109	109	108	108	107	107	106	106	105	105	104	104	101	

