

屋内照明器具特性

品番 (品名)	LGB15552															
光源	LED2700_70_465 x1 465.0 lm															
管理番号	K0151381(0)DB1															
BZ分類	BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	4%	室指数	照明率 (X0.01)																ZCM		
下方光束	96%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	5.6	4.3	3.5	3.0	5.4	4.2	3.5	3.0	5.1	4.1	3.4	2.9	4.9	4.0	3.4	2.9	2.7		
		0.8	6.5	5.4	4.6	4.0	6.4	5.3	4.5	4.0	6.1	5.1	4.4	3.9	5.8	5.0	4.3	3.9	3.6		
		1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.3	4.7	6.7	5.8	5.2	4.6	6.4	5.6	5.0	4.6	4.3		
		1.25	7.8	6.8	6.1	5.5	7.6	6.7	6.0	5.5	7.3	6.5	5.9	5.4	6.9	6.3	5.7	5.3	5.0		
下方投影面積	c m ²	1.5	8.2	7.3	6.6	6.1	8.0	7.2	6.5	6.0	7.7	7.0	6.4	5.9	7.3	6.7	6.2	5.8	5.5		
		2.0	8.8	8.0	7.4	6.9	8.6	7.9	7.3	6.8	8.2	7.6	7.1	6.7	7.9	7.4	7.0	6.6	6.3		
取付高さ	器具間隔最大限		2.5	9.2	8.5	7.9	7.5	9.0	8.4	7.8	7.4	8.6	8.1	7.6	7.3	8.2	7.8	7.4	7.1	6.8	
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.3	7.9	9.2	8.7	8.2	7.8	8.8	8.4	8.0	7.7	8.5	8.1	7.8	7.5	7.2	
H m	1.30 H m	1.30 H m	4.0	9.7	9.3	8.9	8.5	9.5	9.1	8.7	8.4	9.2	8.8	8.5	8.2	8.8	8.6	8.3	8.0	7.7	
			5.0	9.9	9.5	9.2	8.9	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.6	9.1	8.8	8.6	8.4	8.0	7.7
			7.0	10.1	9.9	9.6	9.3	10.0	9.7	9.5	9.2	9.6	9.4	9.2	9.0	9.3	9.1	9.0	8.8	8.4	
			10.0	10.3	10.1	9.9	9.7	10.1	10.0	9.8	9.6	9.8	9.7	9.5	9.4	9.5	9.4	9.2	9.1	8.7	

