

屋内照明器具特性	
品番 (品名)	XLY120ESN
光源	LED5000_85_1450 ×1 1450.0 lm
管理番号	K0155409 (0) DB 1
BZ分類	BZ5

器具効率		100 % 上方光束 6 % 下方光束 94 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.83	0.6	55	42	34	29	53	41	34	28	50	40	33	28	47	38	32	28	25	
			0.81	0.8	64	52	44	38	62	51	44	38	59	49	43	37	56	48	41	37	34	
			0.77	1.0	71	60	52	46	69	58	51	45	65	56	49	44	62	54	48	43	41	
				1.25	77	66	59	53	75	65	58	52	71	62	56	51	67	60	55	50	47	
下方投影面積		cm ²		1.5	81	71	64	58	79	70	63	58	75	67	61	56	71	65	59	55	52	
			等価発光面積	cm ²	2.0	86	78	72	66	84	77	71	66	80	74	69	64	76	71	67	63	59
取付 高さ	器具間隔最大限			2.5	90	83	77	72	88	81	76	71	84	78	74	69	80	75	71	68	64	
	横方向 (A)		縦方向 (B)	3.0	92	86	81	76	90	85	80	75	86	81	77	74	82	78	75	72	68	
1.5m	1.98 m	2.12 m		4.0	96	91	86	82	94	89	85	81	90	86	82	79	86	83	80	77	73	
2	2.62	2.67		5.0	98	94	90	86	96	92	88	85	92	88	85	83	88	85	83	80	76	
2.5	3.26	3.24		7.0	100	97	94	91	98	95	92	90	94	92	89	87	91	89	87	85	81	
3	3.89	3.84		10.0	102	100	97	95	100	98	96	94	96	94	93	91	93	91	90	88	84	

