

屋内照明器具特性	
品番 (品名)	LGBX10003
光源	LED2700_70_470 x1 470.0 lm
管理番号	K0153125(0)DB1
BZ分類	BZ6/0.7/BZ5

器具効率	86%	天井	80%				70%				50%				30%				0%
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	7%	床	10%				10%				10%				10%				0%
下方光束	79%	室指数	照明率 ( X0.01 )																ZCM
保守率	良 中 否 0.67 0.63 0.56	0.6	46	35	28	23	44	34	27	23	41	33	27	22	39	31	26	22	20
		0.8	55	44	37	32	53	43	37	32	50	41	36	31	47	40	34	30	28
		1.0	61	51	44	39	59	50	43	38	55	48	42	37	52	46	41	37	34
		1.25	66	57	51	46	64	56	50	45	60	54	48	44	57	51	47	43	40
下方投影面積	c m <sup>2</sup>	1.5	70	62	56	51	68	60	55	50	64	58	53	49	60	55	51	47	44
		2.0	75	68	63	58	73	67	62	57	69	64	59	56	65	61	57	54	51
取付高さ	器具間隔最大限		2.5	78	72	67	63	76	71	66	62	72	68	64	61	69	65	62	59
	横方向 (A)	縦方向 (B)	3.0	80	75	71	67	78	74	70	66	74	71	67	64	71	68	65	62
H m	1.55 H m	1.55 H m	4.0	83	79	75	72	81	77	74	71	77	74	71	69	74	71	69	67
			5.0	85	81	78	76	83	80	77	74	79	77	74	72	76	73	72	70
			7.0	87	84	82	80	85	82	80	78	81	79	77	76	78	76	75	73
			10.0	88	86	85	83	86	85	83	82	83	81	80	79	79	78	77	76

