

屋内照明器具特性

品番 (品名)	L G W 4 5 9 3 0	
光源	LED2700_70_150 x1	150.0 l m
管理番号	K0151750 (0) DB 1	
B Z 分類	B Z 1 0	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束		10 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	90 %	床	10 %				10 %				10 %				10 %				0 %				
室指数			照明率 (X 0 . 0 1)																Z C M				
保守率	良	0.69	0.6	3.9	2.4	1.4	0.7	3.7	2.3	1.3	0.6	3.3	2.0	1.2	0.6	3.0	1.8	1.1	0.5	2.8	1.6	0.9	0.5
	中	0.67	0.8	4.7	3.1	2.0	1.2	4.4	2.9	1.9	1.1	4.0	2.6	1.7	1.0	3.5	2.4	1.6	0.9	3.2	2.2	1.4	0.9
	否	0.63	1.0	5.3	3.7	2.5	1.6	5.0	3.5	2.4	1.6	4.5	3.2	2.2	1.5	4.0	2.9	2.0	1.4	3.8	2.8	2.0	1.4
下方投影面積	等価発光面積	c m ²	1.25	5.9	4.3	3.2	2.3	5.6	4.2	3.1	2.2	5.0	3.8	2.8	2.0	4.5	3.4	2.6	1.9	4.3	3.4	2.6	1.9
			1.5	6.4	4.9	3.8	2.9	6.1	4.7	3.6	2.8	5.5	4.3	3.4	2.6	4.9	3.9	3.1	2.4	4.7	4.0	3.3	2.8
取付高さ	器具間隔最大限		2.5	7.6	6.5	5.5	4.6	7.3	6.2	5.3	4.5	6.7	5.8	5.0	4.3	6.1	5.3	4.7	4.0	5.8	5.0	4.4	3.5
	横方向 (A)	縦方向 (B)	3.0	8.0	6.9	6.0	5.2	7.7	6.7	5.8	5.1	7.1	6.2	5.5	4.8	6.5	5.8	5.2	4.6	6.2	5.5	4.8	4.0
H m	0.00 H m	0.00 H m	4.0	8.5	7.6	6.8	6.1	8.2	7.4	6.6	6.0	7.6	6.9	6.3	5.7	7.0	6.5	5.9	5.4	6.9	6.3	5.7	4.9
			5.0	8.9	8.1	7.4	6.7	8.6	7.8	7.2	6.6	8.0	7.4	6.8	6.3	7.4	6.9	6.4	6.0	7.4	6.8	6.3	5.4
			7.0	9.3	8.7	8.1	7.6	9.0	8.4	7.9	7.4	8.4	7.9	7.5	7.1	7.9	7.5	7.1	6.8	7.9	7.5	7.1	6.2
			10.0	9.6	9.1	8.7	8.3	9.3	8.9	8.5	8.1	8.8	8.4	8.1	7.7	8.3	8.0	7.7	7.4	8.4	8.1	7.7	6.8

