

屋内照明器具特性	
品番 (品名)	NTS75241S+NTS90551
光源	LED4000_70_3190 ×1 3190.0 lm
管理番号	K0161312 (0) DB 1
BZ分類	BZ5/0.7/BZ4

器具効率		100 % 上方光束 1 % 下方光束 99 %		反射率	天井	80 %					70 %					50 %					30 %					0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %					10 %					10 %					10 %					0 %
					室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	58	46	38	33	56	45	38	33	54	44	37	33	52	43	37	32	30					
			0.63	0.8	68	57	50	44	67	57	49	44	64	55	49	44	62	54	48	44	41					
			0.56	1.0	75	65	58	52	74	64	57	52	71	63	56	52	68	61	56	51	49					
			1.25	81	72	65	60	80	71	65	60	77	69	64	59	74	68	63	58	56						
下方投影面積 等価発光面積		cm ²	1.5	85	77	71	65	84	76	70	65	80	74	69	64	78	72	67	64	61						
			2.0	90	84	78	73	89	83	77	73	86	80	76	72	83	78	74	71	69						
			2.5	94	88	83	79	92	87	82	78	89	85	81	77	86	82	79	76	73						
取付 高さ	器具間隔最大限		3.0	96	91	87	83	94	90	86	82	91	87	84	81	89	85	82	80	77						
	横方向 (A)	縦方向 (B)	4.0	99	95	91	88	97	94	90	87	94	91	88	86	92	89	87	84	82						
H m	0.92 H m	1.22 H m	5.0	101	97	94	91	99	96	93	91	96	94	91	89	94	91	89	87	84						
			7.0	103	100	98	96	101	99	97	95	98	96	95	93	96	94	93	91	88						
			10.0	104	102	101	99	103	101	99	98	100	99	97	96	97	96	95	94	91						

