

屋内照明器具特性	
品番 (品名)	NTS72242S+NTS90200
光源	LED3500_85_1645 ×1 1645.0 lm
管理番号	K0161316 (0) DB1
BZ分類	BZ4

器具効率		100 % 上方光束 1 % 下方光束 99 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	59	48	40	35	58	47	40	35	56	46	40	35	54	45	39	35	33	
			0.77	0.8	70	59	52	47	69	59	52	47	66	57	51	46	64	56	50	46	44	
			0.68	1.0	77	67	60	55	75	66	60	55	72	65	59	54	70	63	58	54	52	
				1.25	83	74	67	62	81	73	67	62	78	71	66	62	75	70	65	61	59	
下方投影面積 等価発光面積		cm ² cm ²		1.5	86	79	73	68	85	78	72	67	82	76	71	67	79	74	70	66	64	
			2.0	92	85	80	76	90	84	79	75	87	82	78	74	84	80	76	73	71		
取付 高さ	器具間隔最大限			2.5	95	89	85	81	93	88	84	80	90	86	82	79	88	84	81	78	76	
	横方向 (A)		縦方向 (B)	3.0	97	92	88	84	95	91	87	84	93	89	86	83	90	87	84	81	79	
H m	0.89 H m		1.20 H m	4.0	100	96	92	89	98	95	92	89	95	92	90	87	93	90	88	86	83	
				5.0	101	98	95	93	100	97	94	92	97	95	92	90	94	92	91	89	86	
				7.0	103	101	99	97	102	100	98	96	99	97	96	94	97	95	94	92	89	
				10.0	105	103	101	100	103	102	100	99	101	99	98	97	98	97	96	95	92	

