

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XLX191AEL                    |
| 光源       | LED3000_85_8130 ×1 8130.0 lm |
| 管理番号     | K0154867 ( 0 ) D 1           |
| BZ分類     | BZ5                          |

| 器具効率     |           | 100 %           |           | 反射率             | 天井                | 80 % |    |     |     | 70 % |    |     |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|-----------------|-----------|-----------------|-------------------|------|----|-----|-----|------|----|-----|----|------|----|----|----|------|----|----|----|-----|
|          |           |                 |           |                 | 壁                 | 70   | 50 | 30  | 10  | 70   | 50 | 30  | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |                 |           |                 | 床                 | 10 % |    |     |     | 10 % |    |     |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |                 |           |                 | 照明率 ( X0.01 ) ZCM |      |    |     |     |      |    |     |    |      |    |    |    |      |    |    |    |     |
| 保守率      |           | 良<br>中<br>否     | 0.81      | 0.6             | 56                | 44   | 36 | 31  | 55  | 43   | 36 | 31  | 53 | 42   | 35 | 30 | 50 | 41   | 35 | 30 | 28 |     |
|          |           |                 | 0.77      | 0.8             | 66                | 55   | 47 | 41  | 65  | 54   | 46 | 41  | 62 | 53   | 46 | 41 | 60 | 51   | 45 | 40 | 38 |     |
|          |           |                 | 0.68      | 1.0             | 73                | 62   | 54 | 48  | 71  | 61   | 54 | 48  | 68 | 60   | 53 | 48 | 66 | 58   | 52 | 47 | 45 |     |
|          |           |                 |           | 1.25            | 79                | 69   | 62 | 56  | 77  | 68   | 61 | 56  | 74 | 66   | 60 | 55 | 71 | 65   | 59 | 55 | 52 |     |
| 下方投影面積   |           | cm <sup>2</sup> |           | 1.5             | 83                | 74   | 67 | 61  | 81  | 73   | 67 | 61  | 78 | 71   | 65 | 61 | 75 | 69   | 64 | 60 | 58 |     |
|          |           |                 | 等価発光面積    | cm <sup>2</sup> | 2.0               | 89   | 81 | 75  | 70  | 87   | 80 | 74  | 70 | 84   | 78 | 73 | 69 | 81   | 76 | 72 | 68 | 66  |
| 取付<br>高さ | 器具間隔最大限   |                 |           | 2.5             | 92                | 86   | 81 | 76  | 91  | 85   | 80 | 75  | 88 | 83   | 78 | 74 | 85 | 81   | 77 | 73 | 71 |     |
|          | 横方向 ( A ) |                 | 縦方向 ( B ) | 3.0             | 95                | 89   | 84 | 80  | 93  | 88   | 84 | 80  | 90 | 86   | 82 | 79 | 88 | 84   | 81 | 78 | 75 |     |
| 1.5m     | 1.92 m    | 1.93 m          | 4.0       | 98              | 94                | 90   | 86 | 97  | 93  | 89   | 86 | 94  | 90 | 87   | 84 | 91 | 88 | 85   | 83 | 80 |    |     |
| 2        | 2.53      | 2.54            | 5.0       | 100             | 96                | 93   | 90 | 99  | 95  | 92   | 89 | 96  | 93 | 90   | 88 | 93 | 91 | 89   | 87 | 84 |    |     |
| 2.5      | 3.13      | 3.14            | 7.0       | 102             | 100               | 97   | 95 | 101 | 99  | 96   | 94 | 98  | 96 | 94   | 92 | 96 | 94 | 92   | 91 | 88 |    |     |
| 3        | 3.76      | 3.77            | 10.0      | 104             | 102               | 100  | 99 | 103 | 101 | 99   | 98 | 100 | 99 | 97   | 96 | 98 | 97 | 95   | 94 | 91 |    |     |

