

屋内照明器具特性	
品番 (品名)	XL X180 NK WJ
光源	LED4000_85_6630 ×1 6630.0 lm
管理番号	K0161230 (2) D 1
BZ分類	BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %							
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M				
下方光束				1 0 0 %																								
保守率		良 中 否	0 . 8 1	0 . 6	6 0	4 9	4 1	3 6	5 9	4 8	4 1	3 6	5 7	4 7	4 1	3 6	5 5	4 6	4 0	3 6	3 4							
			0 . 7 7	0 . 8	7 0	6 0	5 2	4 7	6 9	5 9	5 2	4 7	6 6	5 8	5 1	4 7	6 4	5 6	5 1	4 7	4 5							
			0 . 6 8	1 . 0	7 7	6 7	6 0	5 5	7 5	6 6	6 0	5 5	7 3	6 5	5 9	5 4	7 0	6 3	5 8	5 4	5 2							
				1 . 2 5	8 2	7 4	6 7	6 2	8 1	7 3	6 7	6 2	7 8	7 1	6 6	6 1	7 5	6 9	6 5	6 1	5 9							
下方投影面積		c m ²	1 . 5	8 6	7 8	7 2	6 7	8 5	7 7	7 2	6 7	8 2	7 6	7 0	6 6	7 9	7 4	6 9	6 6	6 3								
			2 . 0	9 1	8 5	7 9	7 5	9 0	8 4	7 9	7 4	8 7	8 2	7 7	7 4	8 4	8 0	7 6	7 3	7 0								
等価発光面積		c m ²	2 . 5	9 5	8 9	8 4	8 0	9 3	8 8	8 3	8 0	9 0	8 6	8 2	7 9	8 8	8 4	8 0	7 8	7 5								
			3 . 0	9 7	9 2	8 8	8 4	9 5	9 1	8 7	8 3	9 2	8 9	8 5	8 2	9 0	8 7	8 4	8 1	7 9								
1 . 5 m		1 . 8 9 m	1 . 8 9 m	4 . 0	1 0 0	9 6	9 2	8 9	9 8	9 5	9 1	8 8	9 5	9 2	9 0	8 7	9 3	9 0	8 8	8 6	8 3							
2		2 . 4 9	2 . 4 9	5 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 2	9 7	9 5	9 2	9 0	9 5	9 3	9 1	8 9	8 6							
2 . 5		3 . 1 2	3 . 1 2	7 . 0	1 0 3	1 0 1	9 9	9 6	1 0 2	1 0 0	9 8	9 6	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 2	9 0							
3		3 . 7 4	3 . 7 4	1 0 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 7	9 6	9 5	9 2							

