

屋内照明器具特性	
品番 (品名)	XLX180NKLJ
光源	LED3000_85_6320 ×1 6320.0 lm
管理番号	K0161230 (2) D 1
BZ分類	BZ4

器具効率		100 %	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) ZCM																
上方光束		0 %	反射率	室指数	0.6	60	49	41	36	59	48	41	36	57	47	41	36	55	46	40	36	34
下方光束		100 %			0.8	70	60	52	47	69	59	52	47	66	58	51	47	64	56	51	47	45
					1.0	77	67	60	55	75	66	60	55	73	65	59	54	70	63	58	54	52
					1.25	82	74	67	62	81	73	67	62	78	71	66	61	75	69	65	61	59
保守率		良 中 否	0.81 0.77 0.68	1.5	86	78	72	67	85	77	72	67	82	76	70	66	79	74	69	66	63	
				2.0	91	85	79	75	90	84	79	74	87	82	77	74	84	80	76	73	70	
下方投影面積		cm ²	2.5	95	89	84	80	93	88	83	80	90	86	82	79	88	84	80	78	75		
等価発光面積		cm ²	3.0	97	92	88	84	95	91	87	83	92	89	85	82	90	87	84	81	79		
取付 高さ	器具間隔最大限			4.0	100	96	92	89	98	95	91	88	95	92	90	87	93	90	88	86	83	
	横方向 (A)		縦方向 (B)	5.0	101	98	95	92	100	97	94	92	97	95	92	90	95	93	91	89	86	
1.5m	1.89 m	1.89 m	7.0	103	101	99	96	102	100	98	96	99	97	96	94	97	95	94	92	90		
2	2.49	2.49	10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	97	96	95	92		
2.5	3.12	3.12																				
3	3.74	3.74																				

