

屋内照明器具特性	
品番 (品名)	L G B 1 2 5 2 1
光源	LED6200_70_3730 ×1 3730.0 lm
管理番号	K0161788 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		7 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		9 3 %																							
保守率		良 中 否	0 . 6 7	0 . 6	5 6	4 4	3 6	3 1	5 4	4 3	3 5	3 0	5 1	4 1	3 5	3 0	4 8	4 0	3 4	2 9	2 7				
			0 . 6 3	0 . 8	6 6	5 4	4 6	4 1	6 4	5 3	4 6	4 0	6 0	5 1	4 4	4 0	5 7	4 9	4 3	3 9	3 6				
			0 . 5 6	1 . 0	7 2	6 1	5 4	4 8	7 0	6 0	5 3	4 8	6 6	5 8	5 2	4 7	6 3	5 6	5 0	4 6	4 3				
				1 . 2 5	7 8	6 8	6 1	5 5	7 6	6 7	6 0	5 5	7 2	6 4	5 8	5 4	6 8	6 2	5 7	5 3	4 9				
下方投影面積		c m ²	1 . 5	8 2	7 3	6 7	6 1	8 0	7 2	6 6	6 0	7 6	6 9	6 4	5 9	7 2	6 6	6 2	5 8	5 4					
			2 . 0	8 8	8 1	7 4	6 9	8 6	7 9	7 3	6 9	8 1	7 6	7 1	6 7	7 8	7 3	6 9	6 5	6 2					
取付高さ	器具間隔最大限		2 . 5	9 1	8 5	8 0	7 5	8 9	8 3	7 9	7 4	8 5	8 0	7 6	7 2	8 1	7 7	7 4	7 0	6 7					
	横方向 (A) 縦方向 (B)		3 . 0	9 4	8 8	8 4	8 0	9 2	8 7	8 2	7 8	8 8	8 3	8 0	7 6	8 4	8 0	7 7	7 4	7 0					
H m	1 . 2 4 H m	1 . 2 4 H m	4 . 0	9 7	9 3	8 9	8 5	9 5	9 1	8 7	8 4	9 1	8 7	8 4	8 2	8 7	8 4	8 2	7 9	7 5					
			5 . 0	9 9	9 5	9 2	8 9	9 7	9 3	9 0	8 8	9 3	9 0	8 7	8 5	8 9	8 7	8 5	8 3	7 8					
			7 . 0	1 0 1	9 8	9 6	9 4	9 9	9 7	9 4	9 2	9 5	9 3	9 1	8 9	9 1	9 0	8 8	8 7	8 2					
			1 0 . 0	1 0 3	1 0 1	9 9	9 7	1 0 1	9 9	9 7	9 6	9 7	9 5	9 4	9 3	9 3	9 2	9 1	9 0	8 5					

