

# 屋内照明器具特性

|         |                   |  |  |  |  |          |  |  |  |  |
|---------|-------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | L S E B 4 0 3 1   |  |  |  |  |          |  |  |  |  |
| 光源      | LED5000_70_453 x1 |  |  |  |  | 453.0 lm |  |  |  |  |
| 管理番号    | K0152279(0)DB1    |  |  |  |  |          |  |  |  |  |
| BZ分類    | BZ6               |  |  |  |  |          |  |  |  |  |

|        |                  |         |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|--------|------------------|---------|------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 器具効率   | 100%             | 天井      | 80%              |      |      |      | 70%  |      |      |      | 50%  |      |      |      | 30%  |      |      |      | 0%   |      |    |
|        | 上方光束             |         | 23%              | 反射率  | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 0% |
|        | 下方光束             |         | 77%              |      | 床    | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |    |
| 室指数    | 照明率 ( X0.01 )    |         |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      | ZCM  |    |
| 保守率    | 良                | 0.63    | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |    |
|        | 中                | 0.6     | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |    |
|        | 否                | 0.56    | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |    |
|        | 0.56             | 0.56    | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |    |
| 下方投影面積 | c m <sup>2</sup> |         | 1.25             | 71   | 60   | 52   | 46   | 68   | 58   | 50   | 44   | 61   | 53   | 47   | 42   | 55   | 48   | 43   | 39   | 33   |    |
|        | 等価発光面積           |         | c m <sup>2</sup> | 1.5  | 75   | 65   | 57   | 51   | 72   | 62   | 55   | 50   | 65   | 57   | 51   | 46   | 58   | 52   | 47   | 43   | 37 |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 85   | 77   | 71   | 65   | 81   | 74   | 68   | 63   | 73   | 68   | 63   | 59   | 67   | 62   | 58   | 55   | 47   |    |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 87   | 80   | 75   | 69   | 83   | 77   | 72   | 67   | 76   | 71   | 66   | 63   | 69   | 65   | 61   | 58   | 51   |    |
| H m    | 1.41H m          | 1.35H m | 4.0              | 91   | 85   | 80   | 76   | 87   | 82   | 77   | 73   | 79   | 75   | 71   | 68   | 72   | 69   | 66   | 63   | 55   |    |
|        |                  |         | 5.0              | 93   | 88   | 84   | 80   | 89   | 85   | 81   | 77   | 81   | 78   | 75   | 72   | 74   | 72   | 69   | 67   | 58   |    |
|        |                  |         | 7.0              | 95   | 92   | 88   | 85   | 91   | 88   | 85   | 82   | 84   | 81   | 79   | 76   | 77   | 75   | 73   | 71   | 62   |    |
|        |                  |         | 10.0             | 97   | 95   | 92   | 90   | 94   | 91   | 89   | 86   | 86   | 84   | 82   | 80   | 79   | 78   | 76   | 74   | 66   |    |

