

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XLX800RHWC                   |
| 光源       | LED4000_85_9160 ×1 9160.0 lm |
| 管理番号     | K0128266 ( 3 ) DB 1          |
| BZ分類     | BZ5                          |

| 器具効率         |                 | 100 %           | 反射率  | 天井                | 80 % |     |    |     | 70 % |    |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |
|--------------|-----------------|-----------------|------|-------------------|------|-----|----|-----|------|----|----|-----|------|----|----|----|------|----|----|----|-----|--|
|              |                 |                 |      | 壁                 | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |
|              |                 |                 |      | 床                 | 10 % |     |    |     | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |
| 上方光束<br>下方光束 |                 | 100 %           | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |    |     |      |    |    |     |      |    |    |    |      |    |    |    |     |  |
| 保守率          |                 | 良<br>中<br>否     | 0.81 | 0.6               | 56   | 43  | 35 | 30  | 54   | 43 | 35 | 30  | 52   | 42 | 35 | 30 | 50   | 41 | 34 | 30 | 28  |  |
|              |                 |                 | 0.77 | 0.8               | 66   | 54  | 46 | 40  | 64   | 53 | 46 | 40  | 62   | 52 | 45 | 40 | 59   | 51 | 44 | 40 | 38  |  |
|              |                 |                 | 1.0  | 73                | 62   | 54  | 48 | 71  | 61   | 53 | 48 | 68  | 59   | 53 | 47 | 65 | 58   | 52 | 47 | 45 |     |  |
|              |                 |                 | 0.68 | 1.25              | 79   | 69  | 61 | 56  | 77   | 68 | 61 | 55  | 74   | 66 | 60 | 55 | 71   | 64 | 59 | 54 | 52  |  |
| 下方投影面積       |                 | cm <sup>2</sup> | 1.5  | 83                | 74   | 67  | 61 | 81  | 73   | 66 | 61 | 78  | 71   | 65 | 60 | 75 | 69   | 64 | 60 | 57 |     |  |
| 等価発光面積       |                 |                 | 2.0  | 89                | 81   | 75  | 70 | 87  | 80   | 74 | 70 | 84  | 78   | 73 | 69 | 81 | 76   | 72 | 68 | 66 |     |  |
| 取付<br>高さ     | 器具間隔最大限         |                 | 2.5  | 93                | 86   | 81  | 76 | 91  | 85   | 80 | 76 | 88  | 83   | 78 | 75 | 85 | 81   | 77 | 74 | 71 |     |  |
|              | 横方向 (A) 縦方向 (B) |                 | 3.0  | 95                | 89   | 85  | 80 | 93  | 88   | 84 | 80 | 91  | 86   | 82 | 79 | 88 | 84   | 81 | 78 | 75 |     |  |
| 1.5m         | 2.13 m          | 2.89 m          | 4.0  | 98                | 94   | 90  | 87 | 97  | 93   | 89 | 86 | 94  | 91   | 87 | 85 | 91 | 88   | 86 | 83 | 81 |     |  |
| 2            | 2.77            | 3.32            | 5.0  | 100               | 97   | 93  | 90 | 99  | 95   | 92 | 90 | 96  | 93   | 91 | 88 | 93 | 91   | 89 | 87 | 84 |     |  |
| 2.5          | 3.41            | 3.82            | 7.0  | 103               | 100  | 97  | 95 | 101 | 99   | 96 | 94 | 98  | 96   | 94 | 93 | 96 | 94   | 93 | 91 | 88 |     |  |
| 3            | 4.06            | 4.36            | 10.0 | 104               | 102  | 100 | 99 | 103 | 101  | 99 | 98 | 100 | 99   | 97 | 96 | 98 | 97   | 95 | 94 | 91 |     |  |

