

屋内照明器具特性	
品番 (品名)	XLX800TELC
光源	LED3000_85_8520 ×1 8520.0 lm
管理番号	K0129806 (2) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		2 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		98 %																					
保守率		良 中 否	0.83	0.6	55	42	34	29	53	42	34	29	51	40	33	28	48	39	33	28	26		
			0.81	0.8	65	53	44	39	63	52	44	38	60	50	43	38	57	49	42	38	35		
			0.77	1.0	71	60	52	46	69	59	51	46	66	57	50	45	63	55	49	45	42		
				1.25	77	67	59	53	75	66	58	53	72	64	57	52	69	62	56	51	49		
下方投影面積		cm ²		1.5	81	72	65	59	79	71	64	58	76	68	62	57	73	66	61	57	54		
				2.0	87	79	72	67	85	78	72	66	82	75	70	65	78	73	68	64	62		
等価発光面積	cm ²		2.5	91	84	78	73	89	82	77	72	85	80	75	71	82	77	73	70	67			
			3.0	93	87	82	77	91	86	81	76	88	83	79	75	85	81	77	74	71			
1.5m	2.1 m	2.89 m		4.0	97	92	87	83	95	90	86	82	91	88	84	81	88	85	82	79	76		
2	2.74	3.34		5.0	99	94	91	87	97	93	90	86	94	90	87	85	91	88	85	83	80		
2.5	3.39	3.85		7.0	101	98	95	92	99	96	94	91	96	94	91	89	93	91	89	87	84		
3	4.03	4.4		10.0	103	101	98	96	101	99	97	95	98	96	95	93	95	94	92	91	88		

