

屋内照明器具特性	
品番 (品名)	XLX800THNC
光源	LED5000_85_9730 ×1 9730.0 lm
管理番号	K0129806 (2) DB 1
BZ分類	BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		2 % 9 8 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 8 3	0 . 6	5 5	4 2	3 4	2 9	5 3	4 2	3 4	2 9	5 1	4 0	3 3	2 8	4 8	3 9	3 3	2 8	2 6	
			0 . 8 1	0 . 8	6 5	5 3	4 4	3 9	6 3	5 2	4 4	3 8	6 0	5 0	4 3	3 8	5 7	4 9	4 2	3 8	3 5	
			0 . 7 7	1 . 0	7 1	6 0	5 2	4 6	6 9	5 9	5 1	4 6	6 6	5 7	5 0	4 5	6 3	5 5	4 9	4 5	4 2	
			1 . 2 5	7 7	6 7	5 9	5 3	7 5	6 6	5 8	5 3	7 2	6 4	5 7	5 2	6 9	6 2	5 6	5 1	4 9		
下方投影面積		c m ²	1 . 5	8 1	7 2	6 5	5 9	7 9	7 1	6 4	5 8	7 6	6 8	6 2	5 7	7 3	6 6	6 1	5 7	5 4		
等価発光面積			c m ²	2 . 0	8 7	7 9	7 2	6 7	8 5	7 8	7 2	6 6	8 2	7 5	7 0	6 5	7 8	7 3	6 8	6 4	6 2	
取付高さ	器具間隔最大限		2 . 5	9 1	8 4	7 8	7 3	8 9	8 2	7 7	7 2	8 5	8 0	7 5	7 1	8 2	7 7	7 3	7 0	6 7		
	横方向 (A) 縦方向 (B)		3 . 0	9 3	8 7	8 2	7 7	9 1	8 6	8 1	7 6	8 8	8 3	7 9	7 5	8 5	8 1	7 7	7 4	7 1		
1 . 5 m	2 . 1 m	2 . 8 9 m	4 . 0	9 7	9 2	8 7	8 3	9 5	9 0	8 6	8 2	9 1	8 8	8 4	8 1	8 8	8 5	8 2	7 9	7 6		
2	2 . 7 4	3 . 3 4	5 . 0	9 9	9 4	9 1	8 7	9 7	9 3	9 0	8 6	9 4	9 0	8 7	8 5	9 1	8 8	8 5	8 3	8 0		
2 . 5	3 . 3 9	3 . 8 5	7 . 0	1 0 1	9 8	9 5	9 2	9 9	9 6	9 4	9 1	9 6	9 4	9 1	8 9	9 3	9 1	8 9	8 7	8 4		
3	4 . 0 3	4 . 4	1 0 . 0	1 0 3	1 0 1	9 8	9 6	1 0 1	9 9	9 7	9 5	9 8	9 6	9 5	9 3	9 5	9 4	9 2	9 1	8 8		

