

屋内照明器具特性	
品番 (品名)	XLX800VELC
光源	LED3000_85_8480 ×1 8480.0 lm
管理番号	K0130922 (5) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		Z CM	
下方光束		100 %																					
保守率		良 中 否	0.81	0.6	56	43	35	29	54	42	35	29	52	41	34	29	50	40	34	29	27		
			0.77	0.8	66	54	46	40	64	53	45	40	61	51	45	39	59	50	44	39	37		
			1.0	1.0	72	61	53	47	71	60	53	47	68	59	52	47	65	57	51	46	44		
			0.68	1.25	78	68	60	55	77	67	60	54	73	65	59	54	70	64	58	53	51		
下方投影面積		cm ²	1.5	82	73	66	60	81	72	65	60	78	70	64	59	75	68	63	59	56			
等価発光面積		cm ²	2.0	88	81	74	69	87	79	73	69	83	77	72	68	80	75	71	67	64			
取付 高さ	器具間隔最大限		2.5	92	85	80	75	90	84	79	74	87	82	77	73	84	80	76	73	70			
	横方向 (A)	縦方向 (B)	3.0	95	89	84	79	93	88	83	79	90	85	81	78	87	83	80	77	74			
1.5m	2.09 m	2.88 m	4.0	98	93	89	86	96	92	88	85	93	90	87	84	91	88	85	82	80			
2	2.72	3.31	5.0	100	96	93	89	98	95	92	89	96	93	90	87	93	90	88	86	83			
2.5	3.35	3.8	7.0	102	99	97	94	101	98	96	93	98	96	94	92	96	94	92	90	87			
3	3.99	4.33	10.0	104	102	100	98	103	101	99	97	100	98	97	96	98	96	95	94	91			

