

# 屋内照明器具特性

品番 (品名)	L S E B 9 0 3 2														
光源	LED2700_70_535 x1 535.0 l m														
管理番号	K0153522(0)D 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	3 %																			
下方光束	97 %																			
室指数	照明率 ( X0.01 ) ZCM																			
保守率	良 0.69 中 0.67 否 0.63	0.6	56	44	36	31	55	43	36	30	52	42	35	30	49	41	34	30	28	
		0.8	66	54	46	41	64	54	46	41	61	52	45	40	58	50	44	40	37	
		1.0	73	62	54	48	71	61	53	48	67	59	52	47	64	57	51	47	44	
		1.25	79	69	61	56	77	68	61	55	73	65	59	54	70	63	58	54	51	
下方投影面積	cm <sup>2</sup>	1.5	83	74	67	61	81	72	66	61	77	70	64	60	74	68	63	59	56	
等価発光面積	cm <sup>2</sup>	2.0	88	81	75	69	86	79	74	69	83	77	72	68	79	74	70	67	63	
取付高さ	器具間隔最大限		2.5	92	85	80	75	90	84	79	74	86	81	77	73	83	79	75	72	69
	横方向 (A)	縦方向 (B)	3.0	94	89	84	79	92	87	83	79	89	84	81	77	86	82	79	76	72
1.5m	1.9 m	1.86 m	4.0	97	93	89	85	96	91	88	84	92	89	85	83	89	86	83	81	77
2	2.54	2.48	5.0	99	96	92	89	98	94	91	88	94	91	89	86	91	89	86	84	81
2.5	3.17	3.09	7.0	102	99	96	94	100	97	95	93	97	94	92	90	93	92	90	88	85
3	3.81	3.71	10.0	103	101	99	97	102	100	98	96	98	97	95	94	95	94	93	92	88

