

屋内照明器具特性	
品番 (品名)	XL X850REWC
光源	LED4000_85_4520 ×1 4520.0 lm
管理番号	K0128266 (3) DB 1
BZ分類	BZ5

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01)																
保守率			良 中 否	0.81	0.6	56	43	35	30	54	43	35	30	52	42	35	30	50	41	34	30	28	
				0.77	0.8	66	54	46	40	64	53	46	40	62	52	45	40	59	51	44	40	38	
				0.68	1.0	73	62	54	48	71	61	53	48	68	59	53	47	65	58	52	47	45	
					1.25	79	69	61	56	77	68	61	55	74	66	60	55	71	64	59	54	52	
下方投影面積			cm ²	1.5	83	74	67	61	81	73	66	61	78	71	65	60	75	69	64	60	57		
				等価発光面積	cm ²	2.0	89	81	75	70	87	80	74	70	84	78	73	69	81	76	72	68	66
取付高さ		器具間隔最大限			2.5	93	86	81	76	91	85	80	76	88	83	78	75	85	81	77	74	71	
		横方向 (A)		縦方向 (B)	3.0	95	89	85	80	93	88	84	80	91	86	82	79	88	84	81	78	75	
1.5m		2.13 m	2.89 m		4.0	98	94	90	87	97	93	89	86	94	91	87	85	91	88	86	83	81	
2		2.77	3.32		5.0	100	97	93	90	99	95	92	90	96	93	91	88	93	91	89	87	84	
2.5		3.41	3.82		7.0	103	100	97	95	101	99	96	94	98	96	94	93	96	94	93	91	88	
3		4.06	4.36		10.0	104	102	100	99	103	101	99	98	100	99	97	96	98	97	95	94	91	

