

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XLX850SEDC                   |
| 光源       | LED6500_85_4800 ×1 4800.0 lm |
| 管理番号     | K0133843 ( 1 ) DR 1          |
| BZ分類     | BZ5                          |

| 器具効率   |  |  | 100 %           |       | 反射率  | 天井  | 80 %          |     |    |     | 70 % |    |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|--|--|-----------------|-------|------|-----|---------------|-----|----|-----|------|----|----|-----|------|----|----|----|------|----|----|----|-----|
|        |  |  |                 |       |      | 壁   | 70            | 50  | 30 | 10  | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |  |  |                 |       |      | 床   | 10 %          |     |    |     | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |  |  |                 |       |      | 室指数 | 照明率 ( X0.01 ) |     |    |     |      |    |    |     |      |    |    |    |      |    |    |    |     |
| 保守率    |  |  | 良<br>中<br>否     | 0.81  | 0.6  | 56  | 43            | 35  | 30 | 54  | 42   | 35 | 29 | 52  | 41   | 34 | 29 | 50 | 40   | 34 | 29 | 27 |     |
|        |  |  |                 | 0.77  | 0.8  | 66  | 54            | 46  | 40 | 64  | 53   | 45 | 40 | 61  | 51   | 45 | 39 | 59 | 50   | 44 | 39 | 37 |     |
|        |  |  |                 | 0.68  | 1.0  | 72  | 61            | 53  | 47 | 70  | 60   | 53 | 47 | 67  | 58   | 52 | 46 | 65 | 57   | 51 | 46 | 44 |     |
|        |  |  |                 |       | 1.25 | 78  | 68            | 60  | 54 | 76  | 67   | 60 | 54 | 73  | 65   | 59 | 54 | 70 | 63   | 58 | 53 | 51 |     |
| 下方投影面積 |  |  | cm <sup>2</sup> | 1.5   | 82   | 73  | 66            | 60  | 81 | 72  | 65   | 60 | 77 | 70  | 64   | 59 | 74 | 68 | 63   | 59 | 56 |    |     |
|        |  |  |                 | 2.0   | 88   | 80  | 74            | 69  | 86 | 79  | 73   | 68 | 83 | 77  | 72   | 67 | 80 | 75 | 71   | 67 | 64 |    |     |
| 等価発光面積 |  |  | cm <sup>2</sup> | 2.5   | 92   | 85  | 79            | 75  | 90 | 84  | 79   | 74 | 87 | 82  | 77   | 73 | 84 | 79 | 76   | 72 | 69 |    |     |
|        |  |  |                 | 3.0   | 94   | 88  | 83            | 79  | 93 | 87  | 83   | 78 | 90 | 85  | 81   | 77 | 87 | 83 | 79   | 76 | 73 |    |     |
| 1.5m   |  |  | 2.08 m          | 2.9 m | 4.0  | 98  | 93            | 89  | 85 | 96  | 92   | 88 | 84 | 93  | 89   | 86 | 83 | 90 | 87   | 84 | 79 |    |     |
| 2      |  |  | 2.71            | 3.31  | 5.0  | 100 | 96            | 92  | 89 | 98  | 95   | 91 | 88 | 95  | 92   | 89 | 87 | 92 | 90   | 88 | 85 |    |     |
| 2.5    |  |  | 3.34            | 3.8   | 7.0  | 102 | 99            | 96  | 94 | 101 | 98   | 95 | 93 | 98  | 95   | 93 | 91 | 95 | 93   | 91 | 90 |    |     |
| 3      |  |  | 3.97            | 4.33  | 10.0 | 104 | 102           | 100 | 98 | 102 | 100  | 99 | 97 | 100 | 98   | 97 | 95 | 97 | 96   | 95 | 93 |    |     |

