

屋内照明器具特性

| | | |
|---------|------------------------------------|--|
| 品番 (品名) | NNLK42762J + FSK41270F + NNL | |
| 光源 | LED5000_85_4290 x1 4290.0 1 m | |
| 管理番号 | K0132394 (2) DB 1 | |
| BZ分類 | BZ4 / 0.9 / BZ3 / 1.8 / BZ4 | |

| | | | | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|------------------|------|-----|-----|------|------|-----|-----|------|------|-----|----|------|------|----|----|-----|-----|----|--|-----|
| 器具効率 | 100 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | | | | |
| | | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | | | |
| 上方光束 | 0 % | 反射率 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | | | | |
| 下方光束 | 100 % | | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | | | |
| | | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.81 | 0.6 | 61 | 50 | 42 | 37 | 60 | 49 | 42 | 37 | 57 | 48 | 42 | 37 | 55 | 47 | 41 | 37 | 35 | | | |
| | 中 | 0.77 | 0.8 | 71 | 61 | 54 | 48 | 70 | 60 | 53 | 48 | 67 | 59 | 53 | 48 | 65 | 57 | 52 | 48 | 46 | | | |
| | 否 | 0.68 | 1.0 | 77 | 68 | 61 | 56 | 76 | 67 | 61 | 56 | 73 | 66 | 60 | 56 | 71 | 64 | 59 | 55 | 53 | | | |
| | | | 1.25 | 83 | 75 | 68 | 63 | 82 | 74 | 68 | 63 | 79 | 72 | 67 | 63 | 76 | 71 | 66 | 62 | 60 | | | |
| 下方投影面積 | c m ² | | 1.5 | 87 | 79 | 73 | 69 | 85 | 78 | 73 | 68 | 83 | 77 | 72 | 68 | 80 | 75 | 71 | 67 | 65 | | | |
| | 等価発光面積 | | c m ² | 2.0 | 92 | 86 | 80 | 76 | 90 | 85 | 80 | 76 | 88 | 83 | 79 | 75 | 85 | 81 | 77 | 74 | 72 | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 95 | 90 | 85 | 81 | 94 | 89 | 84 | 81 | 91 | 87 | 83 | 80 | 88 | 85 | 82 | 79 | 77 | | | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 97 | 93 | 89 | 85 | 96 | 91 | 88 | 84 | 93 | 89 | 86 | 83 | 90 | 87 | 85 | 82 | 80 | | | |
| 1.5m | 1.96 m | 2.06 m | 4.0 | 100 | 96 | 93 | 90 | 98 | 95 | 92 | 89 | 96 | 93 | 90 | 88 | 93 | 91 | 89 | 87 | 84 | | | |
| 2 | 2.59 | 2.57 | 5.0 | 102 | 98 | 96 | 93 | 100 | 97 | 95 | 92 | 98 | 95 | 93 | 91 | 95 | 93 | 91 | 90 | 87 | | | |
| 2.5 | 3.22 | 3.11 | 7.0 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 96 | 100 | 98 | 96 | 95 | 97 | 96 | 94 | 93 | 90 | | | |
| 3 | 3.85 | 3.66 | 10.0 | 105 | 103 | 102 | 100 | 103 | 102 | 101 | 99 | 101 | 100 | 99 | 97 | 99 | 98 | 97 | 96 | 93 | | | |

