

屋内照明器具特性	
品番 (品名)	NNF 2 1 2 3 0 C
光源	LDL20S. N/ 11/ 12 - K(960) ×1 960.0 l m
管理番号	K0125039 (0) DR 1
BZ分類	BZ6/ 0.7/ BZ5/ 8.5/ BZ6

器具効率		97 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		3 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		94 %		室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.81	0.6	52	40	32	27	51	39	32	27	48	38	31	26	46	37	31	26	24
			0.77	0.8	62	50	42	36	60	49	41	36	57	47	40	35	54	46	40	35	32
			1.0	68	57	49	43	66	56	48	42	63	54	47	42	60	52	46	41	39	
			0.68	1.25	74	63	56	50	72	62	55	49	68	60	54	49	65	58	52	48	45
下方投影面積		cm ²	1.5	78	68	61	55	76	67	60	55	72	65	59	54	69	62	57	53	50	
等価発光面積		cm ²	2.0	83	75	69	63	81	74	68	62	78	71	66	61	74	69	64	60	57	
取付 高さ	器具間隔最大限		2.5	87	80	74	69	85	78	73	68	81	76	71	67	78	73	69	65	62	
	横方向 (A) 縦方向 (B)		3.0	89	83	78	73	87	82	77	72	84	79	74	71	80	76	72	69	66	
1.5m	2.01 m	1.91 m	4.0	93	87	83	79	91	86	82	78	87	83	80	76	84	80	77	75	71	
2	2.67	2.51	5.0	95	90	86	83	93	89	85	82	89	86	83	80	86	83	81	78	75	
2.5	3.33	3.12	7.0	97	94	91	88	95	92	89	87	92	89	87	85	89	87	84	83	79	
3	4.02	3.74	10.0	99	96	94	92	97	95	93	91	94	92	90	88	91	89	88	86	83	

