

屋内照明器具特性	
品番 (品名)	NNF 2 1 7 0 0 J
光源	LDL20S. N/ 11 / 12 - K(960) ×1 960.0 l m
管理番号	K0125036 (5) DR 1
B Z 分類	BZ5 / 1.8 / BZ4

器具効率		95 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) Z C M																
保守率		良 中 否	0.81	0.6	53	42	34	29	52	41	34	29	50	40	34	29	48	39	33	29	27	
			0.77	0.8	63	52	45	39	62	52	44	39	59	50	44	39	57	49	43	39	37	
			0.68	1.0	70	60	52	47	68	59	52	47	65	57	51	46	63	56	50	46	44	
				1.25	76	67	60	54	74	66	59	54	71	64	58	54	69	62	57	53	51	
下方投影面積		c m ²	1.5	80	71	65	60	78	71	65	60	75	69	63	59	73	67	62	59	56		
			等価発光面積	c m ²	2.0	85	78	73	68	84	77	72	68	81	75	71	67	78	74	70	66	64
取付 高さ	器具間隔最大限		2.5	89	83	78	74	87	82	77	73	84	80	76	72	82	78	75	72	69		
	横方向 (A)	縦方向 (B)	3.0	91	86	82	78	89	85	81	77	87	83	79	76	84	81	78	75	73		
1.5m	2.07 m	1.91 m	4.0	94	90	86	83	92	89	86	83	90	87	84	82	87	85	82	80	78		
2	2.76	2.51	5.0	96	92	89	87	94	91	89	86	92	89	87	85	89	87	85	83	81		
2.5	3.45	3.11	7.0	98	95	93	91	96	94	92	90	94	92	90	89	91	90	89	87	84		
3	4.15	3.73	10.0	99	97	96	94	98	96	95	93	95	94	93	92	93	92	91	90	87		

