

屋内照明器具特性	
品番 (品名)	NNF 2 2 6 6 6 J
光源	LDL20S. N/ 11 / 12 - K (9 6 0) × 2 9 6 0 . 0 l m
管理番号	K0125017 (0) DR 1
B Z 分類	BZ5 / 0 . 7 / BZ4

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		
下方光束		93 %		Z C M																		
保守率		良 中 否	0.81	0.6	54	43	36	31	53	43	36	31	51	42	35	31	49	41	35	31	29	
			0.77	0.8	64	54	47	42	63	53	46	42	60	52	46	41	58	51	45	41	39	
			0.68	1.0	70	61	54	49	69	60	54	49	66	59	53	49	64	57	52	48	46	
				1.25	76	68	61	56	75	67	61	56	72	65	60	56	69	64	59	55	53	
下方投影面積		c m ²		1.5	80	72	66	62	78	71	66	61	76	70	65	61	73	68	64	60	58	
等価発光面積			c m ²	2.0	85	79	74	69	83	78	73	69	81	76	72	68	78	74	71	67	65	
取付 高さ	器具間隔最大限		2.5	88	83	78	74	87	82	78	74	84	80	76	73	81	78	75	72	70		
	横方向 (A)		縦方向 (B)		3.0	90	86	82	78	89	85	81	78	86	83	79	77	84	81	78	76	73
1.5m	2.01 m	1.93 m	4.0	93	89	86	83	91	88	85	82	89	86	84	81	87	84	82	80	78		
2	2.68	2.54	5.0	94	91	89	86	93	90	88	86	91	88	86	84	88	86	85	83	80		
2.5	3.34	3.15	7.0	96	94	92	90	95	93	91	89	93	91	89	88	90	89	88	86	84		
3	4.02	3.76	10.0	98	96	95	93	96	95	94	92	94	93	92	91	92	91	90	89	86		

