

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 4 9
光源	LDA13L - G / Z100E / S / W ×1 1520.0 l m
管理番号	K0167838 (1) DB 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率		96 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	49	38	30	25	47	36	29	24	43	34	27	23	39	31	26	22	18
			0.63	0.8	58	47	39	34	56	45	38	33	51	42	36	31	46	39	33	29	25
			0.56	1.0	65	54	46	41	62	52	45	40	56	48	42	37	51	44	39	35	31
				1.25	70	61	53	48	67	58	52	46	61	54	48	44	56	50	45	41	36
下方投影面積 等価発光面積		c m ² c m ²		1.5	74	66	59	53	71	63	57	52	65	58	53	49	59	54	50	46	40
				2.0	80	73	67	62	77	70	65	60	70	65	60	57	64	60	56	53	47
				2.5	84	78	72	68	80	75	70	66	74	69	65	62	68	64	61	58	51
取付 高さ	器具間隔最大限			3.0	86	81	76	72	83	78	74	70	76	72	69	66	70	67	64	61	55
	横方向 (A)	縦方向 (B)		4.0	89	85	81	78	86	82	79	75	79	76	73	71	73	70	68	66	59
H m	1.22 H m	1.22 H m		5.0	91	88	84	81	88	85	82	79	81	78	76	74	75	73	71	69	62
				7.0	93	91	88	86	90	87	85	83	83	81	80	78	77	75	74	73	65
				10.0	95	93	91	90	92	90	88	87	85	84	82	81	79	78	76	75	67

