

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 5 3
光源	LDA13L - G / Z100E / S / W ×1 1520.0 l m
管理番号	K0168588 (0) DB 1
B Z 分類	BZ7 / 0.7 / BZ6

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	44	32	24	19	41	30	23	19	36	27	21	17	32	24	19	15	12
			0.63	0.8	53	41	34	28	49	39	32	27	44	35	29	25	39	32	27	23	18
			0.56	1.0	59	48	40	35	55	46	39	33	49	41	35	31	43	37	32	28	23
				1.25	64	54	47	41	61	52	45	40	54	47	41	37	48	42	37	34	28
下方投影面積 等価発光面積		c m ²		1.5	68	59	52	47	64	56	50	45	57	51	46	41	51	46	41	38	31
				2.0	73	66	59	54	69	63	57	52	62	57	52	48	55	51	47	44	37
				2.5	77	70	64	60	73	67	62	57	65	60	56	53	58	55	51	48	41
取付 高さ	器具間隔最大限			3.0	79	73	68	64	75	70	65	61	68	63	60	56	60	57	54	51	43
	横方向 (A)	縦方向 (B)		4.0	82	77	73	69	78	74	70	66	71	67	64	61	63	61	58	56	47
H m	1.92 H m	1.92 H m		5.0	84	80	76	73	80	76	73	70	72	69	67	64	65	63	61	59	50
				7.0	86	83	80	78	82	80	77	74	75	72	70	68	67	66	64	62	53
				10.0	88	86	84	81	84	82	80	78	76	75	73	72	69	68	67	65	56

