

屋内照明器具特性	
品番 (品名)	LGB57585K
光源	LDA13L-G/Z100E/S/W×5 1520.0lm
管理番号	K0164511(0)DB1
BZ分類	BZ6

器具効率		88 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
					室指数		照明率 (X0.01)																			
保守率		良 中 否	0.67	0.6	44	33	26	21	42	32	25	21	38	29	24	19	34	27	22	18	15					
			0.63	0.8	52	42	34	29	50	40	33	28	45	37	31	27	41	34	29	25	21					
			0.56	1.0	58	48	40	35	55	46	39	34	50	42	36	32	45	39	34	30	26					
				1.25	63	54	47	41	60	51	45	40	54	47	42	37	49	43	39	35	30					
下方投影面積		cm ²		1.5	67	58	51	46	64	56	49	44	58	51	46	42	52	47	43	39	34					
			等価発光面積		cm ²		2.0	72	64	58	53	68	62	56	51	62	57	52	48	57	52	48	45	39		
取付高さ	器具間隔最大限						2.5	75	68	63	58	72	66	61	56	65	60	56	53	60	56	52	49	43		
		横方向 (A)	縦方向 (B)		3.0	77	71	66	62	74	69	64	60	68	63	59	56	62	58	55	52	46				
H m	1.41 H m	1.40 H m		4.0	80	76	71	68	77	73	69	65	71	67	64	61	65	62	59	57	50					
				5.0	82	78	74	71	79	75	72	69	72	69	67	64	66	64	62	60	53					
				7.0	84	81	78	76	81	78	76	73	75	72	70	68	69	67	65	63	56					
				10.0	86	84	82	80	83	81	79	77	77	75	73	72	71	69	68	67	59					

