

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 7 6
光源	L E D 2 7 0 0 _ 7 0 _ 3 5 5 × 1 3 5 5 . 0 l m
管理番号	K 0 1 6 9 1 8 8 (1) D R 1
B Z 分類	B Z 1

器具効率	1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束	1 1 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束	8 9 %																				
保守率	良	0 . 6 3	0 . 6	7 9	7 3	6 8	6 5	7 8	7 2	6 8	6 5	7 5	7 0	6 7	6 4	7 3	6 9	6 6	6 4	6 2	
	中	0 . 6	0 . 8	8 5	7 9	7 5	7 2	8 4	7 8	7 5	7 2	8 1	7 7	7 3	7 1	7 8	7 5	7 2	7 0	6 8	
	否	0 . 5 6	1 . 0	8 9	8 4	8 0	7 7	8 8	8 3	7 9	7 7	8 4	8 1	7 8	7 5	8 2	7 8	7 6	7 4	7 1	
			1 . 2 5	9 3	8 8	8 4	8 2	9 1	8 7	8 3	8 1	8 7	8 4	8 1	7 9	8 4	8 1	7 9	7 7	7 5	
下方投影面積	c m ²		1 . 5	9 5	9 1	8 7	8 5	9 3	8 9	8 6	8 4	8 9	8 6	8 4	8 2	8 6	8 4	8 2	8 0	7 7	
等価発光面積	c m ²		2 . 0	9 8	9 4	9 1	8 9	9 5	9 2	9 0	8 8	9 2	8 9	8 7	8 5	8 8	8 6	8 5	8 3	7 9	
取付 高さ	器具間隔最大限		2 . 5	9 9	9 6	9 4	9 2	9 7	9 4	9 2	9 0	9 3	9 1	8 9	8 8	8 9	8 8	8 6	8 5	8 1	
	横方向 (A)	縦方向 (B)	3 . 0	1 0 0	9 8	9 5	9 4	9 8	9 6	9 4	9 2	9 4	9 2	9 1	8 9	9 0	8 9	8 8	8 7	8 2	
H m	0 . 4 9 H m	0 . 4 9 H m	4 . 0	1 0 2	1 0 0	9 8	9 6	9 9	9 8	9 6	9 5	9 5	9 4	9 3	9 1	9 1	9 0	8 9	8 8	8 4	
			5 . 0	1 0 2	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 6	9 5	9 4	9 3	9 2	9 1	9 0	9 0	8 5	
			7 . 0	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 7	9 6	9 5	9 4	9 3	9 2	9 2	9 1	8 6	
			1 0 . 0	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	9 8	9 7	9 6	9 6	9 3	9 3	9 2	9 2	8 7	

