

屋内照明器具特性	
品番 (品名)	LGB16476
光源	LED2700_70_355 ×1 355.0 lm
管理番号	K0169188 (1) DR1
BZ分類	BZ1

器具効率	100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
			床	10 %				10 %				10 %				10 %				0 %				
上方光束	11 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束	89 %																							
保守率	良 中 否	0.63	0.6	79	73	68	65	78	72	68	65	75	70	67	64	73	69	66	64	62				
		0.6	0.8	85	79	75	72	84	78	75	72	81	77	73	71	78	75	72	70	68				
			1.0	89	84	80	77	88	83	79	77	84	81	78	75	82	78	76	74	71				
		0.56	1.25	93	88	84	82	91	87	83	81	87	84	81	79	84	81	79	77	75				
下方投影面積	c m ²		1.5	95	91	87	85	93	89	86	84	89	86	84	82	86	84	82	80	77				
		等価発光面積	c m ²	2.0	98	94	91	89	95	92	90	88	92	89	87	85	88	86	85	83	79			
取付 高さ	器具間隔最大限		2.5	99	96	94	92	97	94	92	90	93	91	89	88	89	88	86	85	81				
	横方向 (A)	縦方向 (B)	3.0	100	98	95	94	98	96	94	92	94	92	91	89	90	89	88	87	82				
H m	0.49 H m	0.49 H m	4.0	102	100	98	96	99	98	96	95	95	94	93	91	91	90	89	88	84				
			5.0	102	101	99	98	100	99	97	96	96	95	94	93	92	91	90	90	85				
			7.0	103	102	101	100	101	100	99	98	97	96	95	94	93	92	92	91	86				
			10.0	104	103	102	102	102	101	100	100	98	97	96	96	93	93	92	92	87				

