

屋内照明器具特性	
品番 (品名)	L G B 1 1 0 8 4
光源	LED2700_70_398 ×1 398.0 l m
管理番号	K0164288 (0) DB 1
B Z 分類	BZ3 / 1.8 / BZ4 / 8.5 / BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		12 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		88 %																						
保守率		良 中 否	0.67	0.6	61	50	44	39	59	49	43	38	56	48	42	38	53	46	41	37	34			
			0.63	0.8	70	61	54	49	68	59	53	48	65	57	51	47	61	55	50	46	43			
			0.56	1.0	76	67	61	56	74	66	60	55	70	63	58	54	66	60	56	52	49			
				1.25	81	73	67	62	79	72	66	61	75	68	63	60	71	65	61	58	54			
下方投影面積 等価発光面積		cm ²		1.5	85	77	71	67	82	76	70	66	78	72	68	64	74	69	65	62	58			
				2.0	89	83	78	74	87	81	76	72	82	77	73	70	78	74	70	68	63			
				2.5	92	87	82	78	90	85	80	77	85	81	77	74	80	77	74	71	67			
取付 高さ	器具間隔最大限		3.0	94	89	85	82	92	87	83	80	87	83	80	77	82	79	77	74	69				
	横方向 (A)	縦方向 (B)																						
H m	1.24 H m	1.24 H m	4.0	97	93	89	86	94	91	88	85	89	86	84	81	85	82	80	78	73				
			5.0	98	95	92	89	96	93	90	88	91	88	86	84	86	84	82	81	75				
			7.0	100	98	95	93	98	95	93	91	93	91	89	88	88	87	85	84	78				
			10.0	102	100	98	96	99	98	96	94	94	93	92	90	90	89	87	86	80				

