

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 0
光源	L L D 2 0 0 0 L C B 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 3 0 8 (1) D R 1
B Z 分類	B Z 9 / 0 . 7 / B Z 8

器具効率		7 5 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		3 3 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		4 2 %																							
保守率		良 中 否	0 . 6 3	0 . 6	3 4	2 4	1 8	1 4	3 1	2 3	1 7	1 3	2 6	1 9	1 5	1 1	2 1	1 6	1 2	9	6				
			0 . 6	0 . 8	4 0	3 1	2 5	2 0	3 7	2 9	2 3	1 9	3 1	2 4	2 0	1 6	2 6	2 0	1 7	1 4	9				
			0 . 5 6	1 . 0	4 5	3 6	2 9	2 5	4 1	3 3	2 7	2 3	3 5	2 8	2 4	2 0	2 9	2 4	2 0	1 7	1 1				
				1 . 2 5	4 9	4 1	3 4	2 9	4 5	3 8	3 2	2 8	3 8	3 2	2 8	2 4	3 1	2 7	2 3	2 0	1 4				
下方投影面積		c m ²	1 . 5	5 2	4 4	3 8	3 3	4 8	4 1	3 6	3 1	4 1	3 5	3 1	2 7	3 4	2 9	2 6	2 3	1 6					
等価発光面積			c m ²	2 . 0	5 6	5 0	4 4	3 9	5 2	4 6	4 1	3 7	4 4	3 9	3 5	3 2	3 7	3 3	3 0	2 7	1 9				
取付 高さ	器具間隔最大限		2 . 5	5 9	5 3	4 8	4 4	5 5	4 9	4 5	4 1	4 7	4 2	3 9	3 6	3 9	3 6	3 3	3 0	2 2					
	横方向 (A)		縦方向 (B)		3 . 0	6 1	5 6	5 1	4 7	5 7	5 2	4 8	4 4	4 8	4 5	4 1	3 8	4 1	3 8	3 5	3 3	2 4			
H m	1 . 6 1 H m	1 . 6 6 H m	4 . 0	6 4	5 9	5 5	5 2	5 9	5 5	5 2	4 9	5 1	4 8	4 5	4 2	4 3	4 0	3 8	3 6	2 7					
			5 . 0	6 6	6 2	5 8	5 5	6 1	5 8	5 5	5 2	5 3	5 0	4 7	4 5	4 4	4 2	4 0	3 8	2 9					
			7 . 0	6 8	6 5	6 2	5 9	6 3	6 0	5 8	5 6	5 5	5 2	5 0	4 8	4 6	4 5	4 3	4 2	3 1					
			1 0 . 0	6 9	6 7	6 5	6 3	6 5	6 3	6 1	5 9	5 6	5 5	5 3	5 1	4 8	4 7	4 5	4 4	3 3					

