

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 0
光源	L L D 4 0 0 0 L C B 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 4 1 8 (0) D R 1
B Z 分類	B Z 9 / 0 . 7 / B Z 8

器具効率		8 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 3	0 . 6	3 8	2 7	2 1	1 6	3 5	2 5	1 9	1 5	2 9	2 2	1 6	1 3	2 4	1 8	1 4	1 1	6	
			0 . 6	0 . 8	4 5	3 5	2 8	2 2	4 1	3 2	2 6	2 1	3 5	2 7	2 2	1 8	2 9	2 3	1 8	1 5	1 0	
			0 . 5 6	1 . 0	5 0	4 0	3 3	2 7	4 6	3 7	3 1	2 6	3 9	3 2	2 6	2 2	3 2	2 6	2 2	1 9	1 3	
				1 . 2 5	5 5	4 5	3 8	3 3	5 0	4 2	3 6	3 1	4 2	3 6	3 1	2 7	3 5	3 0	2 6	2 2	1 5	
下方投影面積		c m ²	1 . 5	5 8	4 9	4 3	3 7	5 4	4 6	4 0	3 5	4 5	3 9	3 4	3 0	3 8	3 3	2 9	2 6	1 8		
			等価発光面積	c m ²	2 . 0	6 3	5 5	4 9	4 4	5 8	5 1	4 6	4 1	4 9	4 4	3 9	3 6	4 1	3 7	3 3	3 0	2 2
取付 高さ	器具間隔最大限		2 . 5	6 6	5 9	5 4	4 9	6 1	5 5	5 0	4 6	5 2	4 7	4 3	4 0	4 4	4 0	3 7	3 4	2 4		
	横方向 (A)	縦方向 (B)	3 . 0	6 8	6 2	5 7	5 3	6 3	5 8	5 3	4 9	5 4	5 0	4 6	4 3	4 5	4 2	3 9	3 6	2 7		
H m	1 . 6 1 H m	1 . 6 6 H m	4 . 0	7 1	6 6	6 2	5 8	6 6	6 2	5 8	5 4	5 7	5 3	5 0	4 7	4 8	4 5	4 3	4 0	3 0		
			5 . 0	7 3	6 9	6 5	6 1	6 8	6 4	6 1	5 8	5 9	5 6	5 3	5 0	5 0	4 7	4 5	4 3	3 2		
			7 . 0	7 6	7 2	6 9	6 6	7 0	6 7	6 5	6 2	6 1	5 8	5 6	5 4	5 2	5 0	4 8	4 6	3 5		
			1 0 . 0	7 7	7 5	7 2	7 0	7 2	7 0	6 8	6 6	6 3	6 1	5 9	5 7	5 4	5 2	5 1	4 9	3 7		

