

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 1
光源	LLD2000LCB1 ×1 531.0 lm
管理番号	K0175296 (0) DR 1
B Z 分類	B Z 4

器具効率		38 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 (X0.01)																			
保守率		良 中 否	0.63	0.6	20	16	14	12	19	16	13	11	18	14	12	11	16	13	11	10	9					
			0.6	0.8	24	20	18	16	23	19	17	15	21	18	16	14	19	16	15	13	12					
			0.56	1.0	26	23	20	18	25	22	20	18	23	20	18	17	20	18	17	16	14					
				1.25	29	25	23	21	27	24	22	20	25	22	20	19	22	20	19	18	15					
下方投影面積		cm ²	1.5	30	27	25	23	29	26	24	22	26	24	22	21	23	22	20	19	17						
等価発光面積				cm ²	2.0	32	29	28	26	30	28	26	25	27	26	24	23	25	24	22	21	19				
取付高さ	器具間隔最大限				2.5	33	31	29	28	32	30	28	27	29	27	26	25	26	25	24	23	20				
	横方向 (A)				縦方向 (B)	3.0	34	32	31	29	32	31	29	28	29	28	27	26	27	26	25	24	21			
H m	1.15 H m	1.26 H m	4.0		35	34	32	31	33	32	31	30	30	29	28	28	27	27	26	25	22					
			5.0	36	34	33	32	34	33	32	31	31	30	29	29	28	27	27	26	23						
			7.0	36	35	35	34	35	34	33	33	32	31	30	30	29	28	28	27	24						
			10.0	37	36	36	35	35	35	34	34	32	32	31	31	29	29	28	28	24						

