

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 1
光源	L L D 3 0 0 0 C U 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 8 7 4 8 (0) D R 1
B Z 分類	B Z 4

器具効率		3 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 3	0 . 6	1 9	1 5	1 3	1 1	1 8	1 5	1 2	1 1	1 6	1 3	1 1	1 0	1 5	1 2	1 1	9	8
			0 . 6	0 . 8	2 2	1 9	1 6	1 5	2 1	1 8	1 6	1 4	1 9	1 7	1 5	1 3	1 7	1 5	1 4	1 2	1 1
			0 . 5 6	1 . 0	2 5	2 1	1 9	1 7	2 3	2 0	1 8	1 7	2 1	1 9	1 7	1 6	1 9	1 7	1 6	1 5	1 3
				1 . 2 5	2 7	2 4	2 1	2 0	2 5	2 3	2 1	1 9	2 3	2 1	1 9	1 8	2 1	1 9	1 8	1 7	1 4
下方投影面積		c m ²	1 . 5	2 8	2 5	2 3	2 1	2 7	2 4	2 2	2 1	2 4	2 2	2 1	1 9	2 2	2 0	1 9	1 8	1 6	
			等価発光面積	c m ²	2 . 0	3 0	2 8	2 6	2 4	2 8	2 6	2 5	2 3	2 6	2 4	2 3	2 2	2 3	2 2	2 1	2 0
取付 高さ	器具間隔最大限		2 . 5	3 1	2 9	2 7	2 6	2 9	2 8	2 6	2 5	2 7	2 5	2 4	2 3	2 4	2 3	2 2	2 1	1 9	
	横方向 (A)	縦方向 (B)	3 . 0	3 2	3 0	2 9	2 7	3 0	2 9	2 7	2 6	2 7	2 6	2 5	2 4	2 5	2 4	2 3	2 2	1 9	
H m	1 . 1 5 H m	1 . 2 6 H m	4 . 0	3 3	3 1	3 0	2 9	3 1	3 0	2 9	2 8	2 8	2 7	2 7	2 6	2 6	2 5	2 4	2 4	2 0	
			5 . 0	3 3	3 2	3 1	3 0	3 2	3 1	3 0	2 9	2 9	2 8	2 7	2 7	2 6	2 6	2 5	2 5	2 1	
			7 . 0	3 4	3 3	3 2	3 2	3 2	3 2	3 1	3 0	2 9	2 9	2 8	2 8	2 7	2 6	2 6	2 6	2 2	
			1 0 . 0	3 4	3 4	3 3	3 3	3 3	3 2	3 2	3 1	3 0	3 0	2 9	2 9	2 7	2 7	2 7	2 6	2 3	

