

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 4
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190461 (0) DR 1
B Z 分類	B Z 3

器具効率		24 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束		7 %	室指数	照明率 (X0.01)																				Z C M	
下方光束		17 %																							
保守率		良 中 否	0.63	0.6	14	11	9	8	13	11	9	8	12	10	8	8	11	9	8	7	6				
			0.6	0.8	16	14	12	11	15	13	11	10	14	12	11	10	13	11	10	9	8				
			0.56	1.0	17	15	14	12	17	15	13	12	15	14	12	11	14	12	11	11	9				
			1.25	19	17	15	14	18	16	15	14	16	15	14	13	15	14	13	12	11					
下方投影面積		cm ²	1.5	20	18	17	15	19	17	16	15	17	16	15	14	16	15	14	13	11					
			2.0	21	19	18	17	20	19	18	17	18	17	16	16	17	16	15	14	13					
等価発光面積		cm ²	2.5	22	20	19	18	21	20	19	18	19	18	17	17	17	16	16	15	13					
			3.0	22	21	20	19	21	20	19	19	19	19	18	17	18	17	16	16	14					
H m	0.60 H m	1.22 H m	4.0	23	22	21	21	22	21	20	20	20	19	19	18	18	18	17	17	15					
			5.0	23	22	22	21	22	22	21	20	20	20	19	19	18	18	18	17	15					
			7.0	24	23	23	22	23	22	22	21	21	20	20	20	19	19	18	18	16					
			10.0	24	24	23	23	23	23	22	22	21	21	20	20	19	19	19	19	16					

