

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 5
光源	L L D 2 0 0 0 L C B 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 3 0 9 (1) D R 1
B Z 分類	B Z 9 / 0 . 9 / B Z 8

器具効率		6 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 4 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		3 4 %																				
保守率		良 中 否	0 . 6 3	0 . 6	3 0	2 2	1 6	1 2	2 7	2 0	1 5	1 1	2 2	1 6	1 2	9	1 8	1 3	1 0	7	4	
			0 . 6	0 . 8	3 6	2 7	2 2	1 7	3 2	2 5	2 0	1 6	2 7	2 1	1 7	1 3	2 1	1 7	1 3	1 1	6	
			0 . 5 6	1 . 0	4 0	3 2	2 6	2 2	3 6	2 9	2 4	2 0	3 0	2 4	2 0	1 7	2 4	1 9	1 6	1 4	8	
				1 . 2 5	4 3	3 6	3 0	2 6	4 0	3 3	2 8	2 4	3 3	2 7	2 3	2 0	2 6	2 2	1 9	1 6	1 0	
下方投影面積		c m ²	1 . 5	4 6	3 9	3 4	2 9	4 2	3 6	3 1	2 7	3 5	3 0	2 6	2 3	2 8	2 4	2 1	1 9	1 2		
等価発光面積			c m ²	2 . 0	5 0	4 4	3 9	3 5	4 6	4 0	3 6	3 2	3 8	3 4	3 0	2 7	3 1	2 7	2 5	2 2	1 5	
取付 高さ	器具間隔最大限		2 . 5	5 2	4 7	4 2	3 9	4 8	4 3	3 9	3 6	4 0	3 6	3 3	3 0	3 3	3 0	2 7	2 5	1 7		
	横方向 (A) 縦方向 (B)		3 . 0	5 4	4 9	4 5	4 2	5 0	4 6	4 2	3 9	4 2	3 8	3 5	3 3	3 4	3 1	2 9	2 7	1 8		
H m	1 . 5 9 H m	2 . 0 9 H m	4 . 0	5 7	5 3	4 9	4 6	5 2	4 9	4 5	4 3	4 4	4 1	3 8	3 6	3 6	3 4	3 2	3 0	2 1		
			5 . 0	5 8	5 5	5 2	4 9	5 4	5 1	4 8	4 5	4 5	4 3	4 1	3 9	3 7	3 5	3 4	3 2	2 2		
			7 . 0	6 0	5 7	5 5	5 2	5 6	5 3	5 1	4 9	4 7	4 5	4 3	4 2	3 9	3 7	3 6	3 5	2 4		
			1 0 . 0	6 1	5 9	5 7	5 6	5 7	5 5	5 3	5 2	4 8	4 7	4 6	4 4	4 0	3 9	3 8	3 7	2 6		

