

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 5
光源	L L D 3 0 0 0 C U 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 8 7 6 3 (0) D R 1
B Z 分類	B Z 9 / 0 . 9 / B Z 8

器具効率		8 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		4 0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		4 0 %																				
保守率		良 中 否	0 . 6 3	0 . 6	3 6	2 6	1 9	1 5	3 2	2 4	1 8	1 4	2 7	1 9	1 5	1 1	2 1	1 6	1 2	9	5	
			0 . 6	0 . 8	4 2	3 2	2 6	2 1	3 9	3 0	2 4	1 9	3 2	2 5	2 0	1 6	2 5	2 0	1 6	1 3	8	
			0 . 5 6	1 . 0	4 7	3 8	3 1	2 6	4 3	3 5	2 8	2 4	3 5	2 9	2 4	2 0	2 8	2 3	1 9	1 6	1 0	
				1 . 2 5	5 2	4 3	3 6	3 1	4 7	3 9	3 3	2 8	3 9	3 3	2 8	2 4	3 1	2 6	2 3	2 0	1 2	
下方投影面積		c m ²	1 . 5	5 5	4 7	4 0	3 5	5 0	4 3	3 7	3 2	4 1	3 6	3 1	2 7	3 3	2 9	2 5	2 2	1 4		
等価発光面積			c m ²	2 . 0	5 9	5 2	4 6	4 1	5 4	4 8	4 3	3 8	4 5	4 0	3 6	3 2	3 6	3 3	2 9	2 7	1 7	
取付高さ	器具間隔最大限		2 . 5	6 2	5 6	5 0	4 6	5 7	5 2	4 7	4 3	4 8	4 3	3 9	3 6	3 9	3 5	3 2	3 0	2 0		
	横方向 (A)		縦方向 (B)	3 . 0	6 4	5 9	5 4	4 9	5 9	5 4	5 0	4 6	5 0	4 6	4 2	3 9	4 0	3 7	3 5	3 2	2 2	
H m	1 . 5 9 H m	2 . 0 9 H m	4 . 0	6 7	6 3	5 8	5 4	6 2	5 8	5 4	5 1	5 2	4 9	4 6	4 3	4 3	4 0	3 8	3 6	2 4		
			5 . 0	6 9	6 5	6 1	5 8	6 4	6 0	5 7	5 4	5 4	5 1	4 8	4 6	4 4	4 2	4 0	3 8	2 6		
			7 . 0	7 1	6 8	6 5	6 2	6 6	6 3	6 0	5 8	5 6	5 4	5 1	4 9	4 6	4 4	4 3	4 1	2 9		
			1 0 . 0	7 3	7 1	6 8	6 6	6 8	6 6	6 3	6 2	5 8	5 6	5 4	5 3	4 8	4 7	4 5	4 4	3 1		

