

屋内照明器具特性	
品番 (品名)	XLGB81800
光源	LED5000_70_400 ×1 400.0 lm
管理番号	K0171431 (0) DB 1
BZ分類	BZ9 / 0.7 / BZ8

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	0.6	45	33	25	19	42	30	23	18	35	26	20	15	29	21	16	13	8
			0.6	0.8	54	41	33	27	49	38	31	25	41	33	26	21	34	27	22	18	12	
			0.56	1.0	60	48	39	33	55	44	37	31	46	38	31	26	38	31	26	22	15	
				1.25	65	54	46	39	60	50	43	37	51	43	37	32	42	36	31	27	18	
下方投影面積		cm ²	1.5	69	59	51	44	64	55	47	42	54	47	41	36	45	39	34	30	21		
等価発光面積			2.0	75	66	59	52	69	61	55	49	59	52	47	43	49	44	40	36	26		
			2.5	79	71	64	58	73	66	60	54	62	56	52	47	52	47	44	40	29		
取付高さ	器具間隔最大限		3.0	81	74	68	63	76	69	64	59	64	59	55	51	54	50	47	43	32		
H _m	1.61H _m	1.66H _m	4.0	85	79	74	69	79	74	69	65	68	64	60	56	57	54	51	48	35		
			5.0	87	82	77	73	81	77	72	69	70	66	63	60	59	56	54	51	38		
			7.0	90	86	82	79	84	80	77	74	73	70	67	64	62	59	57	55	42		
			10.0	92	89	86	83	86	83	81	78	75	73	70	68	64	62	60	59	45		

