

屋内照明器具特性

品番 (品名)	NNLK82523 + NNL8600ENJ									
光源	LED5000_85_6400 x1 6400.0 lm									
管理番号	K0130919 (8) DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.83	0.6	5.5	4.2	3.4	2.9	5.3	4.2	3.4	2.9	5.1	4.0	3.3	2.8	4.8	3.9	3.3	2.8	2.6
	中	0.81	0.8	6.5	5.3	4.5	3.9	6.3	5.2	4.4	3.8	6.0	5.0	4.3	3.8	5.7	4.8	4.2	3.7	3.5
	否	0.77	1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.6	6.6	5.7	5.0	4.5	6.2	5.5	4.9	4.4	4.2
			1.25	7.7	6.7	5.9	5.3	7.5	6.6	5.8	5.3	7.1	6.3	5.7	5.2	6.8	6.1	5.6	5.1	4.8
下方投影面積	cm ²		1.5	8.1	7.2	6.5	5.9	7.9	7.0	6.4	5.8	7.5	6.8	6.2	5.7	7.2	6.6	6.0	5.6	5.3
等価発光面積	cm ²		2.0	8.7	7.9	7.2	6.7	8.5	7.7	7.1	6.6	8.1	7.5	6.9	6.5	7.7	7.2	6.8	6.4	6.0
取付高さ	器具間隔最大限		2.5	9.0	8.4	7.8	7.3	8.8	8.2	7.7	7.2	8.5	7.9	7.4	7.0	8.1	7.6	7.2	6.9	6.6
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.7	9.1	8.5	8.0	7.6	8.7	8.2	7.8	7.5	8.4	8.0	7.6	7.3	6.9
1.5m	2.08m	2.88m	4.0	9.6	9.1	8.7	8.3	9.4	9.0	8.6	8.2	9.1	8.7	8.3	8.0	8.7	8.4	8.1	7.8	7.5
2	2.71	3.3	5.0	9.8	9.4	9.0	8.7	9.6	9.3	8.9	8.6	9.3	8.9	8.6	8.4	8.9	8.7	8.4	8.2	7.8
2.5	3.34	3.79	7.0	10.1	9.7	9.5	9.2	9.9	9.6	9.3	9.1	9.5	9.3	9.0	8.8	9.2	9.0	8.8	8.6	8.2
3	3.97	4.32	10.0	10.2	10.0	9.8	9.6	10.1	9.9	9.6	9.5	9.7	9.5	9.4	9.2	9.4	9.2	9.1	9.0	8.6

