

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 2
光源	LLD4000LCB1 ×1 845.0 l m
管理番号	K0176411 (0) DR 1
B Z 分類	BZ4 / 0.9 / BZ3

器具効率		30 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	16	13	11	9	15	12	10	9	14	11	10	8	12	10	9	8	7
			0.6	0.8	19	16	14	12	18	15	13	12	16	14	12	11	14	13	11	10	9
			0.56	1.0	21	18	16	14	20	17	15	14	18	16	14	13	16	14	13	12	11
			1.25	2.2	20	18	17	21	19	17	16	19	17	16	15	17	16	15	14	12	
下方投影面積		cm ²	1.5	23	21	19	18	22	20	19	17	20	19	17	16	18	17	16	15	13	
等価発光面積			cm ²	2.0	25	23	22	20	24	22	21	20	21	20	19	18	19	18	17	17	14
				2.5	26	24	23	22	25	23	22	21	22	21	20	19	20	19	19	18	15
取付高さ	器具間隔最大限			3.0	27	25	24	23	25	24	23	22	23	22	21	20	21	20	19	19	16
	横方向 (A)		縦方向 (B)	4.0	27	26	25	24	26	25	24	23	24	23	22	22	21	21	20	20	17
Hm	1.15Hm		1.25Hm	5.0	28	27	26	25	27	26	25	24	24	23	23	22	22	21	21	20	18
				7.0	28	28	27	27	27	26	26	25	25	24	24	23	22	22	22	21	18
				10.0	29	28	28	27	27	27	27	26	25	25	24	24	23	22	22	22	19

