

屋内照明器具特性	
品番 (品名)	XLGB81906
光源	LED3500_70_220 x1 220.0 lm
管理番号	K0169179 (0) DR1
BZ分類	BZ5/0.7/BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.63	0.6	50	39	32	27	47	37	30	26	39	32	26	23	33	27	23	20	15	
			0.6	0.8	60	49	42	37	55	46	39	35	47	40	35	31	39	34	30	27	21	
			0.56	1.0	66	56	49	44	61	53	46	42	52	46	41	37	44	39	35	32	25	
				1.25	72	63	56	51	66	59	53	48	57	51	46	43	48	43	40	37	29	
下方投影面積		cm ²	1.5	75	67	61	56	70	63	58	53	60	55	50	47	50	47	43	41	31		
			2.0	81	74	69	64	75	69	64	60	64	60	56	53	54	51	48	46	35		
等価発光面積		cm ²	2.5	84	78	73	69	78	73	69	65	67	63	60	57	56	54	51	49	38		
			3.0	86	81	77	73	80	76	72	69	69	66	63	60	58	56	54	52	39		
H _m	0.00H _m	1.67H _m	4.0	89	85	82	78	83	79	76	74	71	69	66	64	60	58	57	55	42		
			5.0	91	87	84	82	84	82	79	77	73	71	69	67	61	60	59	57	43		
			7.0	92	90	88	86	86	84	82	80	74	73	71	70	63	62	61	60	45		
			10.0	94	92	91	89	88	86	85	83	76	75	73	72	64	63	63	62	47		

