

屋内照明器具特性	
品番 (品名)	XLGB81922
光源	LED2700_70_185 ×1 185.0 lm
管理番号	K0169182 (1) DR 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		5 0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		5 0 %																					
保守率		良 中 否	0 . 6 3	0 . 6	5 1	4 0	3 3	2 8	4 7	3 7	3 1	2 6	4 0	3 2	2 7	2 3	3 3	2 8	2 4	2 1	1 6		
			0 . 6	0 . 8	6 0	5 0	4 3	3 7	5 6	4 7	4 0	3 6	4 7	4 0	3 5	3 2	4 0	3 5	3 1	2 8	2 1		
			0 . 5 6	1 . 0	6 6	5 7	5 0	4 5	6 2	5 3	4 7	4 2	5 2	4 6	4 1	3 8	4 4	4 0	3 6	3 3	2 5		
				1 . 2 5	7 2	6 3	5 7	5 2	6 7	5 9	5 4	4 9	5 7	5 1	4 7	4 4	4 8	4 4	4 1	3 8	2 9		
下方投影面積		c m ²	1 . 5	7 6	6 8	6 2	5 7	7 0	6 4	5 8	5 4	6 0	5 5	5 1	4 8	5 1	4 7	4 4	4 2	3 2			
			2 . 0	8 1	7 5	6 9	6 5	7 5	7 0	6 5	6 1	6 4	6 0	5 7	5 4	5 4	5 1	4 9	4 7	3 6			
取付高さ	器具間隔最大限		2 . 5	8 4	7 9	7 4	7 0	7 8	7 3	6 9	6 6	6 7	6 4	6 1	5 8	5 7	5 4	5 2	5 0	3 8			
	横方向 (A)	縦方向 (B)	3 . 0	8 6	8 2	7 7	7 4	8 0	7 6	7 3	6 9	6 9	6 6	6 3	6 1	5 8	5 6	5 4	5 2	4 0			
H m	0 . 0 0 H m	1 . 6 3 H m	4 . 0	8 9	8 5	8 2	7 9	8 3	8 0	7 7	7 4	7 1	6 9	6 7	6 5	6 0	5 9	5 7	5 6	4 2			
			5 . 0	9 1	8 8	8 5	8 2	8 4	8 2	7 9	7 7	7 3	7 1	6 9	6 7	6 1	6 0	5 9	5 8	4 4			
			7 . 0	9 3	9 0	8 8	8 6	8 6	8 4	8 3	8 1	7 4	7 3	7 2	7 0	6 3	6 2	6 1	6 0	4 5			
			1 0 . 0	9 4	9 2	9 1	8 9	8 8	8 6	8 5	8 4	7 6	7 5	7 4	7 3	6 4	6 3	6 3	6 2	4 6			

