

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 1 0
光源	L L D 5 0 0 0 L C C 1 × 1 1 1 4 0 . 0 l m
管理番号	K 0 1 8 8 4 0 4 (0) D B 1
B Z 分類	B Z 3

器具効率		1 0 0 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		2 %		室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		9 8 %																							
保守率		良 中 否	0 . 6 7	0 . 6	6 4	5 3	4 7	4 2	6 3	5 3	4 6	4 2	6 0	5 2	4 6	4 1	5 8	5 0	4 5	4 1	3 9				
			0 . 6 3	0 . 8	7 4	6 4	5 8	5 3	7 2	6 4	5 7	5 3	7 0	6 2	5 7	5 2	6 7	6 1	5 6	5 2	5 0				
			0 . 5 6	1 . 0	8 0	7 2	6 5	6 1	7 9	7 1	6 5	6 0	7 6	6 9	6 4	6 0	7 3	6 7	6 3	5 9	5 7				
				1 . 2 5	8 5	7 8	7 2	6 8	8 4	7 7	7 2	6 7	8 1	7 5	7 0	6 7	7 8	7 3	6 9	6 6	6 4				
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 9	8 2	7 7	7 3	8 7	8 1	7 6	7 2	8 4	7 9	7 5	7 1	8 2	7 7	7 3	7 0	6 8					
			2 . 0	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 9	8 9	8 5	8 1	7 8	8 6	8 3	7 9	7 7	7 4					
			2 . 5	9 6	9 2	8 8	8 4	9 5	9 0	8 7	8 3	9 2	8 8	8 5	8 2	8 9	8 6	8 3	8 1	7 8					
取付 高さ	器具間隔最大限		3 . 0	9 8	9 4	9 0	8 7	9 7	9 3	9 0	8 7	9 4	9 0	8 8	8 5	9 1	8 8	8 6	8 4	8 1					
	横方向 (A)	縦方向 (B)	4 . 0	1 0 1	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 6	9 4	9 1	8 9	9 3	9 1	8 9	8 8	8 5					
H m	1 . 2 6 H m	1 . 2 5 H m	5 . 0	1 0 2	9 9	9 7	9 5	1 0 0	9 8	9 6	9 4	9 7	9 5	9 4	9 2	9 5	9 3	9 1	9 0	8 7					
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	9 9	9 8	9 6	9 5	9 6	9 5	9 4	9 3	9 0					
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 0	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2					

