

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 1 1
光源	L L D 4 0 0 0 L C B 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 5 5 9 8 (1) D 1
B Z 分類	B Z 1 0

器具効率 上方光束 下方光束		8 0 % 8 0 % 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 7	0 . 6	3 4	2 6	2 1	1 7	2 9	2 2	1 8	1 5	2 0	1 5	1 3	1 1	1 1	9	7	6	0				
			0 . 6 3	0 . 8	4 1	3 3	2 7	2 3	3 5	2 8	2 4	2 0	2 3	1 9	1 6	1 4	1 3	1 1	1 0	8	0				
			0 . 5 6	1 . 0	4 5	3 8	3 2	2 8	3 8	3 2	2 8	2 5	2 6	2 2	1 9	1 7	1 5	1 3	1 1	1 0	0				
				1 . 2 5	4 9	4 2	3 7	3 3	4 2	3 6	3 2	2 9	2 9	2 5	2 2	2 0	1 6	1 4	1 3	1 2	0				
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	5 2	4 6	4 1	3 7	4 4	3 9	3 5	3 2	3 0	2 7	2 5	2 3	1 7	1 6	1 4	1 3	0				
				2 . 0	5 6	5 1	4 6	4 3	4 8	4 4	4 0	3 7	3 3	3 0	2 8	2 6	1 9	1 7	1 6	1 5	0				
取付 高さ	器具間隔最大限			2 . 5	5 8	5 4	5 0	4 7	5 0	4 6	4 3	4 1	3 4	3 2	3 0	2 9	2 0	1 9	1 8	1 7	0				
	横方向 (A) 縦方向 (B)			3 . 0	6 0	5 6	5 3	5 0	5 2	4 8	4 6	4 3	3 5	3 4	3 2	3 0	2 0	1 9	1 9	1 8	0				
H m	0 . 2 0 H m	0 . 2 0 H m		4 . 0	6 2	5 9	5 6	5 4	5 4	5 1	4 9	4 7	3 7	3 5	3 4	3 3	2 1	2 1	2 0	1 9	0				
				5 . 0	6 4	6 1	5 9	5 7	5 5	5 3	5 1	4 9	3 8	3 7	3 5	3 4	2 2	2 1	2 1	2 0	0				
				7 . 0	6 5	6 3	6 1	6 0	5 6	5 5	5 3	5 2	3 9	3 8	3 7	3 6	2 3	2 2	2 2	2 1	0				
				1 0 . 0	6 6	6 5	6 4	6 2	5 7	5 6	5 5	5 4	4 0	3 9	3 8	3 8	2 3	2 3	2 2	2 2	0				

