

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 1 1
光源	L L D 4 0 0 0 L C S 1 × 1 8 3 0 . 0 l m
管理番号	K 0 1 8 1 8 8 8 (0) D R 1
B Z 分類	B Z 5

器具効率		71 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	40	31	26	22	39	31	25	22	37	30	25	21	35	29	25	21	20				
			0.63	0.8	47	38	33	29	46	38	32	28	44	37	32	28	42	36	31	28	26				
			1.0	1.0	51	43	38	34	50	43	37	33	48	42	37	33	46	40	36	33	31				
			0.56	1.25	55	48	43	39	54	47	42	38	52	46	42	38	50	45	41	38	36				
下方投影面積		cm ²	1.5	58	52	46	42	57	51	46	42	55	49	45	42	52	48	44	41	39					
			2.0	62	56	52	48	61	56	51	48	58	54	50	47	56	52	49	46	44					
等価発光面積		cm ²	2.5	65	60	56	52	63	59	55	52	61	57	54	51	59	55	53	50	48					
			3.0	66	62	58	55	65	61	58	55	63	59	56	54	61	58	55	53	51					
Hm	1.24Hm	1.24Hm	4.0	69	65	62	59	67	64	61	59	65	62	60	58	63	61	59	57	54					
			5.0	70	67	64	62	69	66	64	61	67	64	62	60	65	63	61	59	57					
			7.0	72	69	67	65	71	69	67	65	68	67	65	63	66	65	63	62	60					
			10.0	73	71	70	68	72	70	69	67	70	69	67	66	68	67	66	65	62					

